

EVERCOAT®

PREMIUM PAINT FINISHING



Four Products. One System.

PREMIUM PAINT FINISHING

FOUR PRODUCTS. ONE SYSTEM.

The Evercoat Premium Paint Finishing system is a technically advanced system for refinishing professionals. These high-quality products provide the user with time-saving applications and deliver a durable and exceptional high-gloss finish, producing a true "show car shine" every time!

All products in the Premium Paint Finishing system are ...

- Water soluble for quick and easy clean-up
- Safe for use on all paint finishes
- Body shop safe



TRIPLE CUT COMPOUND

- Easily removes 1200 grit and finer sand scratches and produces a low swirl finish
- Unique multi-phase abrasive breaks down during use providing a high-gloss, haze-free surface

Part No.	Size	Units Per Case
100019	QUART	12



TRIPLE GLAZE

- Specially formulated to remove 3000 to 4000 grit wet sand scratches and compound swirl marks
- Produces a high-gloss, swirl-free finish

Part No.	Size	Units Per Case
100030	QUART	6



TRIPLE GLOSS

- Removes micro-fine scratches and provides paint protection with exceptional gloss
- Easy-to-use finishing glaze formulated to achieve the ultimate wet look finish
- Works great on dark colors

Part No.	Size	Units Per Case
100032	QUART	6



TRIPLE MIST

- Exceptional for final wipe down to achieve a brilliant show car appearance.
- Quickly removes smudges, fingerprints, compound dust and other finishing residues
- Excellent lubricant for Clay Magic®

Part No.	Size	Units Per Case
100035	22 fl oz. SPRAYER	12

FINISHING SYSTEM

STEP 1

- Apply sparingly to a 2' x 2' area
 - Buff with a wool pad, or foam compounding pad at 1400 – 1800 rpm
(For light colors use a medium foam pad to eliminate swirl marks and enhance gloss)
- TIP:** To enhance the workability of Triple Cut Compound, spray a small amount of water onto surface or pad before buffing.

STEP 2

- Apply sparingly to a 2' x 2' area
 - Buff with a medium foam polishing pad at 1400 – 1800 rpm
(For removal of swirl marks, use medium pressure, or use light pressure for polishing)
- TIP:** For light colors, use a fine foam polishing pad at 1200 – 1400 rpm as a final step.

STEP 3


- Apply sparingly to a 2' x 2' area
 - Use an Ultra Fine Foam Polishing Pad at 1400 – 1600 rpm
(To eliminate fine swirl marks use medium pressure followed by light pressure to enhance gloss)
- TIP:** Can be used as a hand glaze.

STEP 4 (OPTIONAL)

- Shake lightly
- Apply sparingly onto a cool dry surface 2' x 2' at a time
- Working evenly, use a clean microfiber towel
- Hand buff to a high gloss finish

PREMIUM PAINT FINISHING SYSTEM

EVERCOAT®

<p>019</p> <p>TRIPLE CUT COMPOUND</p> <p>Apply a small amount to work a 2'x2' area.</p> 	<p>WOOL PAD</p>	<p>MEDIUM FOAM PAD</p>	<p>FINE SWIRL MARKS AND SCRATCHES</p>	<p>COMPOUND AND POLISH RESIDUE</p>
<p>030</p> <p>TRIPLE GLAZE</p> <p>Apply a small amount to area being polished</p> 		<p>MEDIUM FOAM PAD</p>	<p>FINE FOAM PAD</p>	
<p>032</p> <p>TRIPLE GLOSS</p> <p>Apply a small amount to area being polished</p> 			<p>ULTRA FINE FOAM PAD (DARK COLORS)</p>	<p>HIGH QUALITY MICROFIBER TOWEL (APPLY BY HAND)</p>
<p>035</p> <p>TRIPLE MIST</p> <p>Lightly mist entire area</p> 				<p>HIGH QUALITY MICROFIBER TOWEL</p>

EVERCOAT®

a division of Illinois Tool Works Inc. | 6600 Cornell Road | Cincinnati, OH 45242 | (800) 729-1530
 Made and Printed in the U.S. | ©2008 Evercoat

evercoat.com

704119 (1208)