



Material Safety Data Sheet

Copyright, 2011, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M (TM) Headlight Lens Restoration System, PN 39008, 39033, 39078, 39086

MANUFACTURER: 3M

DIVISION: Automotive Aftermarket

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 12/30/11

Supersedes Date: 05/27/10

Document Group: 26-6473-8

ID Number(s):

60-4550-4650-2, 60-4550-4818-5, 60-4550-4908-4, 60-4550-4940-7, 60-4550-5356-5, 60-4550-6402-6

This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are:

24-5413-0

Revision Changes:

Page Heading: Product name was modified.

Kit: Product name was modified.

Kit: ID Number(s) was modified.

Section 1: Manufacturer name was added.

Section 16: Disclaimer (first paragraph) was added.

Section 16: Disclaimer (second paragraph) was added.

Section 16: Web address was added.

Section 1: Address was added.

Copyright was added.

Company logo was added.

Telephone header was added.

Company Telephone was added.

Section 1: Emergency phone information was added.

Company Logo was deleted.

Copyright was deleted.

Kit: Manufacturer's name was deleted.

Kit: Emergency phone information was deleted.

Kit: Disclaimer (first paragraph) was deleted.

Kit: Disclaimer (second paragraph) was deleted.

Kit: Address line 1 was deleted.

Kit: Address line 2 was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M™ Rubbing Compound PN 05973, 05974, 05968 39002, 39005, 5974T
MANUFACTURER: 3M
DIVISION: Automotive Aftermarket
ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 12/04/12
Supersedes Date: 10/07/11

Document Group: 24-5413-0

Product Use:

Intended Use: Automotive

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
WATER	7732-18-5	30 - 60
SILICA	7631-86-9	15 - 40
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	10 - 30
KAOLINITE	1318-74-7	3 - 7
SOLVENT-REFINED HEAVY PARAFFINIC PETROLEUM DISTILLATES	64741-88-4	1 - 5
OLEIC ACID	112-80-1	1 - 5
QUARTZ SILICA	14808-60-7	< 3
IIIITE	12173-60-3	0.5 - 1.5
MINERAL OIL	64741-89-5	< 1.5
GLYCERIN	56-81-5	0.5 - 1.5
POLY(OXYETHYLENE)SORBITAN MONOSTEARATE	9005-67-8	0.1 - 1.0

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: Light brown. Slight solvent odor.

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause target organ effects. Contains a chemical or chemicals which can cause cancer.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Prolonged or repeated exposure may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Silicosis: Signs/symptoms may include breathlessness, weakness, chest pain, persistent cough, increased amounts of sputum, and heart disease.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Class Description</u>	<u>Regulation</u>
QUARTZ SILICA	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	SEQ677	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	SEQ677	Known human carcinogen	National Toxicology Program Carcinogens

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature	<i>No Data Available</i>
Flash Point	≥ 150 °F [<i>Test Method: Closed Cup</i>]
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
OSHA Flammability Classification:	Class IIIA Combustible Liquid

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Water may be used to blanket the fire. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Dispose of collected material as soon as possible.

Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid skin contact. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Do not breathe vapors. Do not breathe dust. Avoid contact with oxidizing agents. Avoid breathing of dust created by sanding, grinding or machining.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Store away from areas where product may come into contact with food or pharmaceuticals. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Provide appropriate local exhaust ventilation on open containers. Use in an enclosed process area is recommended. Do not use in a confined area or areas with little or no air movement. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields

Indirect Vented Goggles

.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Neoprene

Nitrile Rubber

.

8.2.3 Respiratory Protection

Do not breathe vapors. Do not breathe dust. Avoid breathing of dust created by sanding, grinding or machining.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
Aluminum, insoluble compounds	ACGIH	TWA, respirable fraction	1 mg/m3	
Benzene, 1,3-dimethyl-	ACGIH	TWA	100 ppm	
Benzene, 1,3-dimethyl-	ACGIH	STEL	150 ppm	
Benzene, 1,4-dimethyl-	ACGIH	TWA	100 ppm	
Benzene, 1,4-dimethyl-	ACGIH	STEL	150 ppm	
Benzene, dimethyl-	ACGIH	TWA	100 ppm	
Benzene, dimethyl-	ACGIH	STEL	150 ppm	
Benzene, dimethyl-	OSHA	TWA	435 mg/m3	
Benzene, trimethyl-	ACGIH	TWA	25 ppm	
Chromium	ACGIH	TWA, as Cr	0.5 mg/m3	
Chromium	OSHA	TWA, as Cr	1 mg/m3	
Copper	ACGIH	TWA, as Cu, fume	0.2 mg/m3	
Copper	ACGIH	TWA, as Cu dust or mist	1 mg/m3	
Copper	OSHA	TWA, as Cu, fume	0.1 mg/m3	
Copper	OSHA	TWA, as Cu dust or mist	1 mg/m3	
GLYCERIN	ACGIH	TWA, as mist	10 mg/m3	
GLYCERIN	OSHA	TWA, respirable fraction	5 mg/m3	
GLYCERIN	OSHA	TWA, as total dust	15 mg/m3	
Hexane	ACGIH	TWA	50 ppm	Skin Notation*
Hexane	OSHA	TWA	1800 mg/m3	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	CMRG	TWA	165 ppm	
JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR	ACGIH	TWA, as total hydrocarbon vapor, non-aerosol	200 mg/m3	Skin Notation*
Kerosine (petroleum)	ACGIH	TWA, as total hydrocarbon vapor, non-aerosol	200 mg/m3	Skin Notation*
Manganese	ACGIH	TWA, as Mn	0.2 mg/m3	
Manganese	OSHA	CEIL, as Mn fume	5 mg/m3	
MANGANESE COMPOUNDS	OSHA	CEIL, as Mn	5 mg/m3	
Mercury	ACGIH	TWA, as Hg	0.025 mg/m3	Skin Notation*
Mercury	OSHA	CEIL	0.1 mg/m3	
MINERAL OILS, HIGHLY-REFINED OILS	ACGIH	TWA, inhalable fraction	5 mg/m3	
Octane	ACGIH	TWA	300 ppm	
Octane	OSHA	TWA	2350 mg/m3	
Octane, all isomers	ACGIH	TWA	300 ppm	
Paraffin oil	OSHA	TWA, as mist	5 mg/m3	
PETROLEUM DISTILLATES	OSHA	TWA	2000 mg/m3	
QUARTZ SILICA	ACGIH	TWA, respirable fraction	0.025 mg/m3	
QUARTZ SILICA	OSHA	TWA concentration, respirable	0.1 mg/m3	
QUARTZ SILICA	OSHA	TWA concentration, as total dust	0.3 mg/m3	
Selenium	ACGIH	TWA, as Se	0.2 mg/m3	
SELENIUM COMPOUNDS	ACGIH	TWA, as Se	0.2 mg/m3	
SELENIUM COMPOUNDS	OSHA	TWA, as Se	0.2 mg/m3	
SILICA	CMRG	TWA, as respirable dust	3 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA concentration	0.8 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA	20 millions of particles/cu. ft.	

SOLVENT-REFINED HEAVY PARAFFINIC PETROLEUM DISTILLATES	CMRG	TWA	5 mg/m3
Stoddard solvent	ACGIH	TWA	100 ppm
Stoddard solvent	OSHA	TWA	2900 mg/m3

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists
 CMRG: Chemical Manufacturer Recommended Guideline
 OSHA: Occupational Safety and Health Administration
 AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor, Color, Grade:	Light brown. Slight solvent odor.
General Physical Form:	Liquid
Autoignition temperature	<i>No Data Available</i>
Flash Point	>= 150 °F [<i>Test Method:</i> Closed Cup]
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Boiling Point	> 150 °F [<i>Test Method:</i> ASTM METHOD]
Density	1.19 - 1.21 g/ml
Vapor Density	<i>No Data Available</i>
Vapor Pressure	14.7 mmHg [@ 20 °C] [<i>Test Method:</i> ASTM METHOD]
Specific Gravity	1.19 - 1.21 [<i>Ref Std:</i> WATER=1]
pH	7.5 - 8.5
Melting point	<i>Not Applicable</i>
Solubility in Water	Negligible
Evaporation rate	<i>No Data Available</i>
Hazardous Air Pollutants	0.003 lb HAPS/lb solids [<i>Test Method:</i> Calculated]
Volatile Organic Compounds	15.4 % weight [<i>Test Method:</i> calculated per CARB title 2]
Volatile Organic Compounds	185 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Kow - Oct/Water partition coef	<i>No Data Available</i>
Percent volatile	58.23 %
VOC Less H2O & Exempt Solvents	388 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Viscosity	6,000 - 10,000 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat
 Sparks and/or flames

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance

Formaldehyde
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D018 (Benzene)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):

LB-K100-0431-7, LB-K100-0684-1, LB-K100-0838-6, 60-4550-3563-8, 60-4550-3564-6, 60-4550-3565-3, 60-4550-3575-2, 60-4550-4631-2, 60-4550-5064-5, 60-4550-5065-2, 60-4550-5066-0, 60-4550-5071-0, 60-4550-5072-8, 60-4550-5073-6

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

STATE REGULATIONS

Contact 3M for more information.

CALIFORNIA PROPOSITION 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	None	**Carcinogen

** WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS. Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 Flammability: 2 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 8: Respiratory protection - recommended respirators information was modified.

Section 8: Respiratory protection - recommended respirators was modified.

Section 9: Property description for optional properties was modified.

Section 8: Respiratory protection - recommended respirators guide was modified.

Section 14: ID Number(s) Template 1 was modified.

Section 2: Ingredient table was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 15: California proposition 65 ingredient information was modified.

Copyright was modified.

Section 8: Respiratory protection - recommended respirators punctuation was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely

within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com