

Revision date : 2015/01/19 Version: 3.0

Page: 1/12 (30220935/CDU\_GEN\_US/EN)

### 1. Substance/preparation and company identification

<u>Company</u> BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA 24 Hour Emergency Response Information CHEMTREC: 1-800-424-9300 BASF HOTLINE: 1-800-832-HELP (4357)

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Specific target organ toxicity - repeated exposu	2	Auditory
		organ
Flammable aerosols	1	
Hazardous to the aquatic environment - acute	3	
Flammable liquids	2	

Label elements

Pictogram: Flame Health hazard

Signal Word: Danger

Hazard Statement: H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H373 May cause damage to organs through prolonged

H229 Pressurized container: May burst if heated.

Precautionary Statements (Prevention):P260Do not breathe dust or mist.P211Do not spray on an open flame or other

ignition source. P240 Ground/bond container and receiving equipment.

P233Keep container tightly closed.P243Take precautionary measures against static

Revision date : 2015/01/19 Page: 2/12 Version: 3.0 (30220935/CDU\_GEN\_US/EN) discharge. Use explosion-proof P241 electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. P251 P280 Wear protective gloves/protective clothing/eye protection/face protection. Precautionary Statements (Response): P314 Get medical advice/attention if you feel unwell. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P370 + P378 In case of fire: Use water spray for extinction. Precautionary Statements (Storage): P403 + P235 Store in a well-ventilated place. Keep cool. P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F. Precautionary Statements (Disposal): P501 Dispose of contents/container to hazardous or special waste collection point. Hazards not otherwise classified No applicable information available. According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200 Emergency overview EXTREMELY FLAMMABLE COMPRESSED GAS Flammable aerosol HARMFUL IF INHALED CAN CAUSE CENTRAL NERVOUS SYSTEM DAMAGE CAN CAUSE LIVER DAMAGE CAN CAUSE KIDNEY DAMAGE MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION SUSPECT CANCER HAZARD MAY CAUSE PULMONARY EDEMA INGESTION MAY CAUSE GASTRIC DISTURBANCES

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Revision date : 2015/01/19 Version: 3.0 Page: 3/12 (30220935/CDU\_GEN\_US/EN)

CAS Number Weight % Chemical name 5.0 - 7.0 % xylene 1.0 - 3.0 % ethylbenzene 1330-20-7 100-41-4 According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200 CAS Number Weiqht % Chemical name 115-10-6 50.0 - 75.0 % dimethyl ether 108-65-6 10.0 - 15.0 % 1-methoxy-2-propyl acetate 123-86-4 10.0 - 15.0 % n-butylacetate 5.0 - 7.0 % xylene 1.0 - 3.0 % ethyl 3-ethoxypropionate 1330-20-7 763-69-9 1.0 - 3.0 % ethylbenzene 100-41-4

4. First-Aid Measures

Description of first aid measures

General advice: First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

If inhaled: Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin: Wash affected areas with water for at least 15 minutes. If symptoms persist, seek medical advice.

If in eyes: Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention. If swallowed: Rinse mouth and then drink plenty of water. Do not induce vomiting due to aspiration hazard. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention is required.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

Revision date : 2015/01/19 Version: 3.0

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: Dry extinguishing media Carbon dioxide Foam Water spray

Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting: Aerosol container contains flammable gas under pressure. Vapors and/or decomposition products are irritants and/or toxic. If product is heated above decomposition temperatures, acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information: Vapors are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Flash fire may occur. Remove product from areas of fire or otherwise cool sealed containers with water in order to avoid pressure build-up due to heat. Do not flood burning material with water due to potential spreading of fire. Contain contaminated water/firefighting water. Run-off water from fire may cause pollution. Notify proper authorities.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures Extinguish sources of ignition nearby and downwind. Wear suitable personal protective clothing and equipment.

Revision date : 2015/01/19 Version: 3.0 Page: 5/12 (30220935/CDU\_GEN\_US/EN)

Ensure adequate ventilation. Avoid prolonged inhalation. Avoid contact with skin and eyes. Use antistatic tools.

Environmental precautions Do not discharge into drains/surface waters/groundwater. A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

Methods and material for containment and cleaning up Dike spillage. Place into appropriately labeled waste containers. Spills should be contained, solidified, and placed in suitable containers for disposal.

#### 7. Handling and Storage

Precautions for safe handling Ensure adequate ventilation. Do not puncture, drop or slide containers. Use static lines when mixing and transferring material. Handle and open container with care. Avoid contact with the skin, eyes and clothing. WARNING: Empty containers may still contain hazardous residue. Do not apply to hot surfaces. Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Protection against fire and explosion: Use antistatic tools. Exhaust fans should be explosion proof. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up. Risk of explosion if heated under confinement. Avoid all sources of ignition: heat, sparks, or open flame. Conditions for safe storage, including any incompatibilities Segregate from incompatible substances. Segregate from oxidizing agents. Segregate from strong bases. Segregate from strong acids. Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight. Consult local fire marshal for storage requirements. Storage stability:

Revision date : 2015/01/19 Version: 3.0 Page: 6/12 (30220935/CDU\_GEN\_US/EN)

#### 8. Exposure Controls and Personal Protection

Components with occupational exposure limits ethylbenzene ACGIH STEL 125 ppm; TWA 100 ppm PEL 100 ppm 435 mg/m3 OSHA n-butylacetate STEL 200 ppm; TWA 150 ppm ACGIH OSHA PEL 150 ppm 710 mg/m3 xylene STEL 150 ppm; TWA 100 ppm PEL 100 ppm 435 mg/m3 ACGIH OSHA PEL 100 ppm 435 mg/m3

Advice on system design: Provide local exhaust ventilation to maintain recommended P.E.L. General mechanical ventilation should comply with OSHA 1910.94.

Personal protective equipment

Respiratory protection: Wear respiratory protection if ventilation is inadequate. Wear NIOSH-certified (or equivalent) organic vapor respirator. Particulate filters should be added during spray operations. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection: Use appropriate chemically resistant gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection: Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection: Body protection must be chosen based on activity level and exposure.

General safety and hygiene measures: Work place should be equipped with a shower and eye wash. Contact lenses should not be worn. Remove contaminated clothing. Contaminated equipment or clothing should be cleaned after each use or disposed of. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form: Odour:

aerosol
solvent-like

Revision date : 2015/01/19 Version: 3.0 Page: 7/12 (30220935/CDU\_GEN\_US/EN)

Colour: colourless pH value: No applicable information available.			
Melting temperature: No applicable information available.			
Boiling range: 13- °F / 25.0- °C			
Sublimation temperature: No applicable information available.			
Flash point: < 42- °F (< 41.1- °C)			
+/- 3 °F Setaflash Closed Cup (measured)			
Flammability: No applicable information available.			
Lower explosion limit: 3.4 %(V)			
Upper explosion limit: 18.0 %(V)			
Autoignition: No applicable information available.			
Vapour pressure: not available			
Density: 6.05 Lb/USg CALC	6.05 Lb/USq CALC		
Relative density: 0.72			
Vapour density: heavier than air			
Partitioning coefficient			
n-octanol/water (log Pow): No applicable information available.			
Thermal decomposition: No applicable information available.			
Viscosity, dynamic: No applicable information available.			
Solids content: approx. 0 % / 0.2507 %(V)			
Viscosity, kinematic: > 20.60 mm2/s			
Solubility in water: No applicable information available.			
<pre>% volatiles: approx. 99.6 % / 99.7 %(V)</pre>			
Solubility (quantitative): No applicable information available.			
Solubility (qualitative): No applicable information available.			
Evaporation rate: No applicable information available.			

10. Stability and Reactivity

Reactivity

Reactivity: No applicable information available.

Chemical stability

Chemical stability: The product is chemically stable.

Possibility of hazardous reactions

Hazardous reactions: No applicable information available.

Conditions to avoid

Conditions to avoid: Avoid all sources of ignition: heat, sparks or open flames. Avoid electrostatic discharge.

Incompatible materials

Substances to avoid:

Revision date : 2015/01/19 Version: 3.0 Page: 8/12 (30220935/CDU\_GEN\_US/EN)

strong bases strong oxidizing agents strong acids

Hazardous decomposition products

Decomposition products: carbon monoxide carbon dioxide

Thermal decomposition: No applicable information available.

11. Toxicological Information

Primary routes of exposure Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Primary routes of entry: Solvents are absorbed through the skin.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: ethylbenzene Assessment of acute toxicity: Of moderate toxicity after short-term inhalation.

Oral

Acute oral toxicity:

Inhalation

Acute inhalation toxicity: Dermal

Acute dermal toxicity:

Assessment other acute effects

Assessment of STOT single: No applicable information available.

Irritation / corrosion

Revision date : 2015/01/19 Version: 3.0 Page: 9/12 (30220935/CDU\_GEN\_US/EN)

Assessment of irritating effects: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: xylene Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

Sensitization

Assessment of sensitization: No applicable information available.

Aspiration hazard No applicable information available.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Genetic toxicity

Assessment of mutagenicity: No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: ethylbenzene Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Reproductive toxicity

Assessment of reproduction toxicity: No applicable information available.

Development

Assessment of teratogenicity: No applicable information available.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Revision date : 2015/01/19 Version: 3.0 Page: 10/12 (30220935/CDU\_GEN\_US/EN)

#### 12. Ecological Information

No applicable information available.

#### 13. Disposal Considerations

Waste disposal of substance Dispose of in accordance with national, state and local regulations. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA. Do not discharge into drains/surface waters/groundwater. Incinerate or dispose of in a RCRA licensed facility. Do not incinerate closed containers.

Container disposal WARNING: Empty containers may still contain hazardous residue. Facility must be capable of handling empty aerosol cans. Do not cut, puncture, crush, or incinerate empty aerosol containers. Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT	
Hazard class: Packing group:	2.1
ID-number: Proper shipping name:	UN 1950 AEROSOLS
Sea transport IMDG	
Hazard class:	2.1
Packing group: ID-number:	UN 1950
Proper shipping name:	AEROSOLS
Air transport IATA/ICAO	
Hazard class: Packing group:	2.1
ID-number:	UN 1950
Proper shipping name:	AEROSOLS

Revision date : 2015/01/19 Version: 3.0 Page: 11/12 (30220935/CDU\_GEN\_US/EN)

Federal Regulations Registration status TSCA, US released / listed EPCRA 313 CAS number Weight % Chemical name 1330-20-7 6.1 xylene 1.1 ethylbenzene 100-41-4 State regulations State RTK CAS Number Chemical name 115-10-6 dimethyl ether 108-65-6 1-methoxy-2-propyl acetate 123-86-4 n-butylacetate 1330-20-7 xylene 763-69-9 ethyl 3-ethoxypropionate 100-41-4 ethylbenzene CA Prop. 65 WARNING: This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm. HMIS III rating Health: 2<sup>m</sup> Flammability: 4 Physical hazard: 0

16. Other information

SDS prepared by: BASF NA Product Regulations

SDS prepared on 19.01.2015

We support worldwide Responsible Care<sup>®</sup> initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY

Revision date : 2015/01/19 Version: 3.0 Page: 12/12 (30220935/CDU\_GEN\_US/EN)

FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.