

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 1/12
(30233297/CDU_GEN_US/EN)

1. Substance/preparation and company identification

Company

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard;
29 CFR Part 1910.1200

Classification of the product

Skin corrosion/irritation	2
Serious eye damage/eye irritation	2A
Skin sensitization	1
Flammable aerosols	1
Flammable liquids	2
Hazardous to the aquatic environment - acute	2
Hazardous to the aquatic environment - chronic	2

Label elements

Pictogram:

Flame

Exclamation mark

Environment

Signal Word:

Danger

Hazard Statement:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurized container: May burst if heated.

Precautionary Statements (Prevention):

P261 Avoid breathing

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 2/12
(30233297/CDU_GEN_US/EN)

dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P272 Contaminated work clothing should not be allowed out of the workplace.
P211 Do not spray on an open flame or other ignition source.
P240 Ground/bond container and receiving equipment.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P243 Take precautionary measures against static discharge.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P264 Wash with plenty of water and soap thoroughly after handling.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements (Response):

P391 Collect spillage.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
P362 + P364 Take off contaminated clothing and wash before reuse.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use water spray for extinction.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary Statements (Storage):

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 3/12
(30233297/CDU_GEN_US/EN)

No applicable information available.

According to Regulation 1994 OSHA Hazard Communication Standard;
29 CFR Part 1910.1200

Emergency overview

EXTREMELY FLAMMABLE

COMPRESSED GAS

Flammable aerosol

HARMFUL IF INHALED

CAN CAUSE CENTRAL NERVOUS SYSTEM DAMAGE

CAN CAUSE LIVER DAMAGE

CAN CAUSE KIDNEY DAMAGE

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION

SUSPECT CANCER HAZARD

INGESTION MAY CAUSE GASTRIC DISTURBANCES

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard;
29 CFR Part 1910.1200

CAS Number	Weight %	Chemical name
proprietary	3.0 - 5.0 %	Proprietary Acrylated Esters
proprietary	3.0 - 5.0 %	Acrylated Resin
proprietary	3.0 - 5.0 %	Proprietary Acrylated Resin 2
67-64-1	3.0 - 5.0 %	acetone
42978-66-5	3.0 - 5.0 %	tripropyleneglycol diacrylate
78-93-3	1.0 - 3.0 %	methyl ethyl ketone
162881-26-7	0.3 - 1.0 %	phosphine oxide, phenylbis(2,4,6-trimethylbenzo

According to Regulation 1994 OSHA Hazard Communication Standard;
29 CFR Part 1910.1200

CAS Number	Weight %	Chemical name
115-10-6	25.0 - 50.0 %	dimethyl ether
123-86-4	7.0 - 10.0 %	n-butylacetate
7779-90-0	7.0 - 10.0 %	zinc phosphate
7727-43-7	7.0 - 10.0 %	barium sulphate
14807-96-6	7.0 - 10.0 %	talc
67-64-1	3.0 - 5.0 %	acetone
42978-66-5	3.0 - 5.0 %	tripropyleneglycol diacrylate
78-93-3	1.0 - 3.0 %	methyl ethyl ketone
proprietary	1.0 - 3.0 %	Methacrylate Ester Derivative

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 4/12
(30233297/CDU_GEN_US/EN)

transport in stable sideways position (recovery position).
Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air.

If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

Wash affected areas with water for at least 15 minutes.

If symptoms persist, seek medical advice.

If in eyes:

Flush with copious amounts of water for at least 15 minutes.

Hold eyelids open to facilitate rinsing.

If irritation develops, seek medical attention.

Seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water.

Do not induce vomiting due to aspiration hazard.

Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

Immediate medical attention is required.

Most important symptoms and effects, both acute and delayed

Symptoms:

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

Dry extinguishing media

Carbon dioxide

Foam

Water spray

Unsuitable extinguishing media for safety reasons:

water jet

Special hazards arising from the substance or mixture

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 5/12
(30233297/CDU_GEN_US/EN)

Hazards during fire-fighting:

Aerosol container contains flammable gas under pressure.
Vapors and/or decomposition products are irritants and/or toxic.
If product is heated above decomposition temperatures, acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Vapors are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Flash fire may occur.

Remove product from areas of fire or otherwise cool sealed containers with water in order to avoid pressure build-up due to heat.

Do not flood burning material with water due to potential spreading of fire.

Contain contaminated water/firefighting water.

Run-off water from fire may cause pollution.

Notify proper authorities.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Extinguish sources of ignition nearby and downwind.

Wear suitable personal protective clothing and equipment.

Ensure adequate ventilation.

Avoid prolonged inhalation.

Avoid contact with skin and eyes.

Use antistatic tools.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

Methods and material for containment and cleaning up

Dike spillage.

Place into appropriately labeled waste containers.

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure adequate ventilation.

Do not puncture, drop or slide containers.

Use static lines when mixing and transferring material.

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 6/12
(30233297/CDU_GEN_US/EN)

Handle and open container with care.
Avoid contact with the skin, eyes and clothing.
WARNING: Empty containers may still contain hazardous residue.
Do not apply to hot surfaces.
Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces.

Protection against fire and explosion:
Use antistatic tools.
Exhaust fans should be explosion proof.
Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources.
Sealed containers should be protected against heat as this results in pressure build-up.
Risk of explosion if heated under confinement.
Avoid all sources of ignition: heat, sparks, or open flame.

Conditions for safe storage, including any incompatibilities
Segregate from incompatible substances.
Segregate from oxidizing agents.
Segregate from strong bases.
Segregate from strong acids.

Further information on storage conditions:
Keep container tightly closed.
Protect from direct sunlight.
Consult local fire marshal for storage requirements.

Storage stability:

8. Exposure Controls and Personal Protection

Components with occupational exposure limits
acetone

ACGIH STEL 750 ppm; TWA 500 ppm

OSHA PEL 1000 ppm 2400 mg/m³

methyl ethyl ketone

ACGIH STEL 300 ppm; TWA 200 ppm

OSHA PEL 200 ppm 590 mg/m³

n-butylacetate

ACGIH STEL 200 ppm; TWA 150 ppm

OSHA PEL 150 ppm 710 mg/m³

barium sulphate

ACGIH TWA 10 mg/m³

OSHA PEL 5 mg/m³ R; PEL 15 mg/m³ T

talc

ACGIH TWA 2 mg/m³

R Respirable fraction

T Total dust

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 7/12
(30233297/CDU_GEN_US/EN)

General mechanical ventilation should comply with OSHA 1910.94.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate.
Wear NIOSH-certified (or equivalent) organic vapor respirator.
Particulate filters should be added during spray operations.
Do not exceed the maximum use concentration for the respirator
facepiece/cartridge combination.
Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:

Use appropriate chemically resistant gloves as determined by an
evaluation of glove performance characteristics and the hazards
and potential hazards identified, including but not limited to
butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Tightly fitting safety goggles (chemical goggles).
Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen based on activity level and
exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and eye wash.
Contact lenses should not be worn.
Remove contaminated clothing.
Contaminated equipment or clothing should be cleaned after each
use or disposed of.
Hands and/or face should be washed before breaks and at the end of
the shift.

9. Physical and Chemical Properties

Form:	aerosol
Odour:	of the solvent contained in the product
Odour threshold:	No applicable information available.
Colour:	white
pH value:	No applicable information available.
Melting temperature:	No applicable information available.
Boiling range:	13- - 257 °F / 25.0- - 125.0 °C
Sublimation temperature:	No applicable information available.
Flash point:	< 1 °F (< 17.2- °C) +/- 3 °F Setaflash Closed Cup (measured)
Flammability:	No applicable information available.
Lower explosion limit:	1.4 %(V)
Upper explosion limit:	18.0 %(V)
Autoignition:	No applicable information available.
Vapour pressure:	91.18 mmHg (20 °C)
Density:	8.03 Lb/USg CALC

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 8/12
(30233297/CDU_GEN_US/EN)

Relative density:	0.96
Vapour density:	heavier than air
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Thermal decomposition:	No applicable information available.
Viscosity, dynamic:	No applicable information available.
Solids content:	approx. 43 % / 22.0196 %(V)
Viscosity, kinematic:	No applicable information available.
Solubility in water:	No applicable information available.
% volatiles:	approx. 52.7 % / 72.4 %(V)
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.

10. Stability and Reactivity

Reactivity

Reactivity:
No applicable information available.

Chemical stability

Chemical stability:
The product is chemically stable.

Possibility of hazardous reactions

Hazardous reactions:
No applicable information available.

Conditions to avoid

Conditions to avoid:
Avoid all sources of ignition: heat, sparks or open flames.
Avoid electrostatic discharge.

Incompatible materials

Substances to avoid:
strong bases
strong oxidizing agents
strong acids
Hazardous decomposition products

Decomposition products:
carbon monoxide
carbon dioxide

Thermal decomposition:
No applicable information available.

11. Toxicological Information

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 9/12
(30233297/CDU_GEN_US/EN)

Primary routes of exposure
Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity:
No applicable information available.

Oral

Acute oral toxicity:

Inhalation

Acute inhalation toxicity:

Dermal

Acute dermal toxicity:

Assessment other acute effects

Assessment of STOT single:
No applicable information available.

Irritation / corrosion

Assessment of irritating effects:
Eye contact causes irritation.
Skin contact causes irritation.

Information on: tripropyleneglycol diacrylate
Assessment of irritating effects:
Eye contact causes irritation.

Sensitization

Assessment of sensitization:
Sensitization after skin contact possible.

Information on: tripropyleneglycol diacrylate
Assessment of sensitization:
Sensitization after skin contact possible.

Aspiration hazard
No applicable information available.

Chronic Toxicity/Effects

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 10/12
(30233297/CDU_GEN_US/EN)

Repeated dose toxicity

Assessment of repeated dose toxicity:
No applicable information available.

Genetic toxicity

Assessment of mutagenicity:
No applicable information available.

Carcinogenicity

Assessment of carcinogenicity:
No applicable information available.

Reproductive toxicity

Assessment of reproduction toxicity:
No applicable information available.

Development

Assessment of teratogenicity:
No applicable information available.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

No applicable information available.

13. Disposal Considerations

Waste disposal of substance

Dispose of in accordance with national, state and local regulations.

The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA.

Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA licensed facility.

Do not incinerate closed containers.

Container disposal

WARNING: Empty containers may still contain hazardous residue. Facility must be capable of handling empty aerosol cans.

Do not cut, puncture, crush, or incinerate empty aerosol containers.

Dispose of in accordance with national, state and local

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 11/12
(30233297/CDU_GEN_US/EN)

regulations.

14. Transport Information

Land transport
USDOT

Hazard class: 2.1
Packing group:
ID-number: UN 1950
Proper shipping name: AEROSOLS

Sea transport
IMDG

Hazard class: 2.1
Packing group:
ID-number: UN 1950
Proper shipping name: AEROSOLS

Air transport
IATA/ICAO

Hazard class: 2.1
Packing group:
ID-number: UN 1950
Proper shipping name: AEROSOLS

15. Regulatory Information

Federal Regulations

Registration status

TSCA, US released / listed

EPCRA 313

CAS number	Weight %	Chemical name
7779-90-0	8.5	zinc phosphate

State regulations

State RTK

CAS Number	Chemical name
115-10-6	dimethyl ether
proprietary	Proprietary Component of BI 156746
123-86-4	n-butylacetate
7779-90-0	zinc phosphate
7727-43-7	barium sulphate
14807-96-6	talc

Safety data sheet

AM826 FLASH FILL UV PRIMER

Revision date : 2015/06/24
Version: 2.0

Page: 12/12
(30233297/CDU_GEN_US/EN)

67-64-1	acetone
42978-66-5	tripropyleneglycol diacrylate
78-93-3	methyl ethyl ketone
TSRN 161090809-6079	Methacrylate Ester Derivative

CA Prop. 65

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

HMIS III rating

Health: 3 $\frac{3}{2}$ Flammability: 4 Physical hazard: 1

16. Other information

SDS prepared by: BASF NA Product Regulations

SDS prepared on 24.06.2015

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.