

PERFORMANCE MASKING TAPE



SMART® Performance Masking Tape meets the standards your shop demands and offers great resistance to UV, solvents, and other liquids. SMART Performance Masking Tape provides excellent adhesion and sticks to a wide variety of irregularly shaped surfaces. Compatible with solvent and waterborne paints, this tape leaves no adhesive when removed.



PHYSICAL PROPERTIES

STANDARD

METRIC

ASTM TEST METHOD

| PHYSICAL PROPERTIES | STANDARD | METRIC | ASTM TEST METHOD |
|--------------------------------------|----------------|-------------------|------------------|
| THICKNESS | 5.4 Mils | 0.137MM | D3652 |
| ADHESION TO STEEL | 26oz/in Width | 28N/100MM Width | D3330 |
| ELONGATION AT BREAK | 9% | 9% | D3759 |
| TENSILE STRENGTH | 22lbs/in Width | 385 N/100MM Width | D3759 |
| SERVICE TEMPERATURE - MAXIMUM | 212°F/30 Mins | 100°C/30 Mins | N/A |

RECOMMENDED STORAGE CONDITIONS

Store in original packaging in a cool, clean, dry place away from direct sunlight and at a temperature of 40°-80°F (4°-26°C) with relative humidity at 40% to 50%.

Always apply tape to clean, dry surfaces that are free of grease, oil, or other contaminants.

| | |
|-------------------------|--|
| BACKING | Saturated Semi-Crepe Paper |
| COLOR | Orange |
| ADHESIVE | Natural Rubber and Cross-Linked Resins |
| AVAILABLE WIDTHS | 18MM (SMT2518) 36MM (SMT2536) |
| AVAILABLE LENGTH | 55M |

The above properties and results obtained refer to the average values of laboratory testing. FinishMaster does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. FinishMaster strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use and assumes no responsibility for any damage or injury sustained as a result of the use of its products.