

PREMIUM MASKING TAPE



SMART® Premium Masking Tape performs where it matters most and is designed to meet the most demanding masking situations. SMART Premium Masking Tape is waterproof, solvent resistant, UV resistant, and withstands high temperatures. It also provides excellent adhesion and sticks to a wide variety of irregularly shaped surfaces. Compatible with solvent and waterborne paints, this tape leaves no adhesive when removed.



PHYSICAL PROPERTIES

STANDARD

METRIC

ASTM TEST METHOD

PHYSICAL PROPERTIES	STANDARD	METRIC	ASTM TEST METHOD
THICKNESS	5.91 Mils	0.150MM	D3652
ADHESION TO STEEL	29oz/in Width	37N/100MM Width	D3330
ELONGATION AT BREAK	9%	9%	D3759
TENSILE STRENGTH	28lbs/in Width	485 N/100MM Width	D3759
SERVICE TEMPERATURE - MAXIMUM	248°F/60 Mins	120°C/60 Mins	N/A

RECOMMENDED STORAGE CONDITIONS

Store in original packaging in a cool, clean, dry place away from direct sunlight and at a temperature of 40°-80°F (4°-26°C) with relative humidity at 40% to 50%.

Always apply tape to clean, dry surfaces that are free of grease, oil, or other contaminants.

BACKING	Saturated Semi-Crepe Paper
COLOR	Blue
ADHESIVE	Natural Rubber and Cross-Linked Resins
AVAILABLE WIDTHS	18MM (SMT3518) 36MM (SMT3536)
AVAILABLE LENGTH	55M

The above properties and results obtained refer to the average values of laboratory testing. FinishMaster does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. FinishMaster strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use and assumes no responsibility for any damage or injury sustained as a result of the use of its products.