



TECHNICAL DATA SHEET
SMT623 SMART Anti-Static Cleaner

Distributed by:
FinishMaster, Inc.
115 W. Washington
Street
Suite 700 S
Indianapolis, IN 46204
317-237-3678

COMPONENTS

SMT623 Smart Anti-Static Cleaner

DESCRIPTION

SMT623 is a ready to use, 0.00lbs/gal VOC waterborne surface cleaner designed specifically for areas with low VOC regulations. SMT623 is medium-drying and is designed to remove tar, wax, oil, grease, road grime, silicone, and surface contaminants prior to sanding or bodywork as well as pre-cleaning before applying topcoats. SMT623 may be used on bare metal without concern for immediate flash rusting and plastic to minimize static build-up.

SURFACE PREPARATION

1. Saturate a clean dry lint-free cloth with SMT623 Smart Anti-Static Cleaner and apply to one panel at a time or for large areas, apply to a 2' x 2' section to avoid premature drying.
2. Follow by wiping with a clean lint-free cloth until dry. Be sure to wipe the surface completely clean and dry. If SMT623 is allowed to dry on the surface, re-apply and dry thoroughly.
3. In low temperature applications, be sure to dry the surface completely before applying primers or topcoats. Additional heat or air movement may be used to speed up the solvent evaporation.

Note: Protect from freezing. Best used when temperatures are maintained at or above 70°F / 21°C. Do not use on solvent sensitive substrates.

POT LIFE

- No pot life restrictions.

PHYSICAL DATA

SMT623	
Film Thickness	N/A
Volume Solids	N/A
VOC Applied	0.00
Flash Point	See SDS

DISPOSAL

Dispose of all paint and paint related materials in accordance with state and local regulations.

SAFETY & HEALTH

Read and follow all technical product information, labels, and SDS prior to application. Keep product out of reach of children and animals. Always wear proper safety equipment (respirator, gloves, eye, and clothing protection) when using this product.