



PRODUCT DATA

4236

Pit-Fill Spot Putty

DESCRIPTION:

To ensure an ultra smooth surface, use Transtar's Pit-Fill Spot Putty. It is a single component polymer based system that air dries to a sandable, durable finish in minutes! Designed for use in filling scratches, pinholes, low spots, blemishes, sanding marks and other surface imperfections. Pit-Fill Spot Putty has excellent adhesion to bare metal, galvanized, aluminum and over other properly prepared existing finishes. Once cured, it can be sanded to a feather-edge and accepts virtually all paint finishes. It features minimal shrinkage and an ultra-smooth consistency.

TECHNICAL DATA :

COLOR:	Buff (Light Beige)
VISCOSITY:	Thixotropic Paste
TACK FREE TIME:	45 - 90 seconds @ 77°F (25°C)
SOLIDS:	> 68%
V.O.C.:	4.09 #/gal. (490 g/l)

APPLICATION:

1. Surface must be clean and free of all dirt and other contaminants. Clean using SCAT #6311, Speedi SCAT #6321 or Aqua SCAT #6351/6354.
2. Sand surface to receive Pit-Fill Spot Putty with 220 grit sandpaper. Reclean with SCAT.
3. Squeeze a small amount of putty from container. Apply a thin coat using a putty knife, spreader or plastic razor blade.
4. Additional thin coats can be applied at 5 - 10 minute intervals as needed.
5. Ready to sand, wet or dry, in 5- 10 minutes at room temperature.
6. For best results, wet sand with 360 grit sandpaper prior to application of primer surfacer or sealer. Surface is now ready for final application of primer surfacer or sealer, followed by topcoat.

SALES POINTS:

- Convenient size and packaging (squeeze and apply!)
- Dries in minutes and easy to sand
- Ready to sand in half the time of other spot putties
- Superior adhesion and featheredging properties
- Excellent adhesion on virtually all substrates (including galvanized)
- Excellent hold-out with minimal shrinkage
- Durable polymer based system
- Easy to close container keeps material clean

COMPETITION:

NitroStan 9000
 3M 05950
 Fibreglass Evercoat 403
 Sikkens Kombi Putty
 Spies Hecker 7715
 Dupont 2286S

DISCLAIMER: The Technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Transtar Autobody Technologies experience and research and is believed to be reliable. As Transtar has no control over conditions in which the product is used, stored , or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.



(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin).

PACKAGE SIZE:

4236 Pit-Fill Spot Putty - 6.75 oz. squeeze tube (200 ml), 6/case
 TRANSTAR AUTOBODY TECHNOLOGIES • 2040 HEISERMAN DRIVE, BRIGHTON, MI 48114 • (800) 824-2843
 FAX (800) 477-7923 • EMAIL: info@tat-co.com