

1 Identification

- **Product identifier**
- **Trade name:** 39592 Metal Bite Finishing Glaze
- **Article number:** 39592
- **Application of the substance / the mixture**
Coating
filler
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 1)

· **Hazard-determining components of labeling:**

styrene

Talc

titanium dioxide

BISPHENOL A DIGLYCIDAL METHACRYLATE

· **Hazard statements**

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

(Contd. on page 3)



Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

· Dangerous components:		
14807-96-6	Talc	30 - 40%
100-42-5	styrene	13 - 30%
1565-94-2	BISPHENOL A DIGLYCIDAL METHACRYLATE	10 - 13%
65997-17-3	Glass	7 - 10%
13463-67-7	titanium dioxide	5 - 7%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

(Contd. on page 5)

Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 4)

100-42-5 styrene

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m ³ , 100 ppm Long-term value: 215 mg/m ³ , 50 ppm
TLV	Short-term value: 170 mg/m ³ , 40 ppm Long-term value: 85 mg/m ³ , 20 ppm BEI

· Ingredients with biological limit values:

100-42-5 styrene

BEI	400 mg/g creatinine Medium: urine Time: end of shift Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)
	0.2 mg/L Medium: venous blood Time: end of shift Parameter: Styrene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145 °C

· Flash point: 31 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 480 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower:	1.2 Vol %
Upper:	8.9 Vol %

· Vapor pressure at 20 °C: 6 hPa

· Density at 20 °C: 1.49135 g/cm³

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Organic solvents:	19.2 %
VOC content:	19.2 %

(Contd. on page 7)



Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 6)

Solids content: 80.8 %
Other information No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

100-42-5 styrene

Oral	LD50	5000 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc	3
100-42-5	styrene	2B
13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide, chemically prepared	3
	BENTONITE	suspected carcinogen <2% 14808-60-7
123-31-9	1,4-dihydroxybenzene	3

· **NTP (National Toxicology Program)**

100-42-5	styrene	R
----------	---------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

USA

(Contd. on page 8)

Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 7)


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Generally not hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1993
- **UN proper shipping name**
- **DOT** Flammable liquids, n.o.s. (Styrene monomer, stabilized)
- **ADR** 1993 Flammable liquids, n.o.s. (Styrene monomer, stabilized), special provision 640E
- **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (STYRENE MONOMER, STABILIZED)
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3

(Contd. on page 9)

Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 8)

· ADR, IMDG, IATA



· Class 3 Flammable liquids
· Label 3

· Packing group III
· DOT, ADR, IMDG, IATA

· Environmental hazards:
· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids
· EMS Number: F-E,S-E
· Stowage Category A

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT
· Quantity limitations On passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L

· ADR
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· IMDG
· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1993 FLAMMABLE LIQUIDS, N.O.S., SPECIAL PROVISION 640E (STYRENE MONOMER, STABILIZED), 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara

· Section 355 (extremely hazardous substances):

123-31-9	1,4-dihydroxybenzene
----------	----------------------

· Section 313 (Specific toxic chemical listings):

14807-96-6	Talc
------------	------

100-42-5	styrene
----------	---------

123-31-9	1,4-dihydroxybenzene
----------	----------------------

(Contd. on page 10)

Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 9)

· TSCA (Toxic Substances Control Act):	
14807-96-6	Talc
100-42-5	styrene
1565-94-2	BISPHENOL A DIGLYCIDAL METHACRYLATE
65997-17-3	Glass
13463-67-7	titanium dioxide
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide
67-64-1	acetone
123-31-9	1,4-dihydroxybenzene

· Proposition 65

· Chemicals known to cause cancer:	
13463-67-7	titanium dioxide

· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	

· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	

· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

· Cancerogenity categories

· EPA (Environmental Protection Agency)	
67-64-1	acetone

· TLV (Threshold Limit Value established by ACGIH)		
14807-96-6	Talc	A4
100-42-5	styrene	A4
13463-67-7	titanium dioxide	A4
67-64-1	acetone	A4
123-31-9	1,4-dihydroxybenzene	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

styrene
Talc
titanium dioxide
BISPHENOL A DIGLYCIDAL METHACRYLATE

(Contd. on page 11)

Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 10)

· **Hazard statements**

- H226 Flammable liquid and vapor.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H335 May cause respiratory irritation.
- H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves / eye protection / face protection.
- P240 Ground/bond container and receiving equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P321 Specific treatment (see on this label).
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 05/31/2016 / 9

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

(Contd. on page 12)



Trade name: 39592 Metal Bite Finishing Glaze

(Contd. of page 11)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

· *** Data compared to the previous version altered.**