

Reviewed on 01/08/2016

1 Identification

Printing date 05/31/2016

- · Product identifier
- · Trade name: 39777 High-Build Self Leveling Seam Sealer
- · Article number: 39777
- · Application of the substance / the mixture Sealant
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225
- · Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

• Emergency telephone number: CHEMTREC 1-800-424-9300

2 *Hazard*(*s*) *identification*

· Classification of the substance or mixture

GHS08 Health hazard



H351 Suspected of causing cancer.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

Hazard-determining components of labeling: bisphenolA(chloro)oxirane polymer Mercaptan Terminated Polymer NJTS 800938 5952 Cellulose POLYMER OF EPICHLOROHYDRIN-POLYGLYCOL
Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation.

(Contd. on page 2)

USA

Printing date 05/31/2016

Reviewed on 01/08/2016

Trade name: 39777 High-Build Self Leveling Seam Sealer

	(Contd. of page 1)
	e an allergic skin reaction.
	l of causing cancer.
	e respiratory irritation.
· Precautionary s	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
<i>P305</i> + <i>P351</i> + <i>P</i> .	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P363	Wash contaminated clothing before reuse.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification s	
· NFPA ratings (
	Iealth = 3
	ire = 1
	Peactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH 3	Health = 3
FIRE 1	Fire = 1
REACTIVITY 0	Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description:

*

Mixture: consisting of the following components. Weight percentages

(Contd. on page 3)



SEM

Page 3/10

Reviewed on 01/08/2016

Trade name: 39777 High-Build Self Leveling Seam Sealer

		(Contd. of page 2)
· Dangerous	components:	
	Mercaptan Terminated Polymer NJTS 800938 5952	13 - 30%
25068-38-6	bisphenolA(chloro)oxirane polymer	13 - 30%
9004-34-6	6 Cellulose	7 - 10%
26142-30-3	POLYMER OF EPICHLOROHYDRIN-POLYGLYCOL	1.5 - 5%
68909-14-8	B Elastomer modified diglycidal ether	1.5 - 5%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1-1.5%
17557-23-2	2 1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	<u>≤</u> 1%
74398-71-3	CASTOR OIL GLYCIDAL ETHER	<u>≤</u> 1%
13463-67-7	7 titanium dioxide	<i>≤1%</i>

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 05/31/2016

Reviewed on 01/08/2016

Trade name: 39777 High-Build Self Leveling Seam Sealer

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling
- No special measures required.
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:
- The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

9004-34-6 Cellulose

- PEL Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
- REL Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
- TLV Long-term value: 10 mg/m³

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Page 4/10

Printing date 05/31/2016

Reviewed on 01/08/2016

Trade name: 39777 High-Build Self Leveling Seam Sealer

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.





Tightly sealed goggles

9 Physical and chemical properties

General Information	
· Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
• Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	261 °C
· Flash point:	249 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	340 °C
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C:	1.60677 g/cm ³

(Contd. of page 4)



Reviewed on 01/08/2016

Trade name: 39777 High-Build Self Leveling Seam Sealer

		(Contd. of page
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
Water:	0.1 %	
Solids content:	95.6 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
13463-67-7	titanium dioxide	2B
	Quartz (SiO2)	1
1333-86-4	Carbon black	2B
7631-86-9	silicon dioxide, chemically prepared	3
64-17-5	ethanol	1
	·	(Contd. on page 7)
		US



Printing date 05/31/2016

Reviewed on 01/08/2016

Trade name: 39777 High-Build Self Leveling Seam Sealer

(Contd. of page 6)

K

· NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number		
DOT, ADR, ADN, IMDG, IATA	Void	
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA		
Class	Void	
Packing group		
DOT, ADR, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	

Page 7/10



Printing date 05/31/2016

Reviewed on 01/08/2016

Trade name: 39777 High-Build Self Leveling Seam Sealer

		(Contd. of page 7)
· Special precautions for user	Not applicable.	
• Transport in bulk according to Annex II MARPOL73/78 and the IBC Code	of Not applicable.	
· UN "Model Regulation":	Void	

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):		
None of the ingredient is listed.		
· Section 313	· Section 313 (Specific toxic chemical listings):	
68909-14-8	Elastomer modified diglycidal ether	
107-21-1	ethanediol	
67-56-1	methanol	
· TSCA (Toxi	c Substances Control Act):	
1317-65-3	GROUND CALCIUM CARBONATE	
25068-38-6	bisphenolA(chloro)oxirane polymer	
9004-34-6	Cellulose	
26142-30-3	POLYMER OF EPICHLOROHYDRIN-POLYGLYCOL	
68909-14-8	Elastomer modified diglycidal ether	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	
17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	
67762-90-7	FUMED SILICA	
	CASTOR OIL GLYCIDAL ETHER	
13463-67-7	titanium dioxide	
	3-aminopropyltriethoxysilane	
	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	
107-21-1	ethanediol	
	Quartz (SiO2)	
	Carbon black	
· Proposition		
	znown to cause cancer:	
	bisphenolA(chloro)oxirane polymer	
	CASTOR OIL GLYCIDAL ETHER	
	titanium dioxide	
	ethanediol	
	Quartz (SiO2)	
1333-86-4	Carbon black	
· Chemicals k	· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.		

(Contd. on page 9) USA



Printing date 05/31/2016

Reviewed on 01/08/2016

Trade name: 39777 High-Build Self Leveling Seam Sealer

		(Contd. of pag
Chemica	ls known to cause reproductive toxicity for males:	
None of t	the ingredients is listed.	
Chemica	ls known to cause developmental toxicity:	
107-21-1	ethanediol	
67-56-1	methanol	
64-17-5	ethanol	
Cancerog	genity categories	
· EPA (En	vironmental Protection Agency)	
None of t	the ingredients is listed.	
TLV (Th	reshold Limit Value established by ACGIH)	
13463-67	7-7 titanium dioxide	A
107-21	1-1 ethanediol	A
14808-60	0-7 Quartz (SiO2)	A
1333-86	5-4 Carbon black	A
64-17	7-5 ethanol	A
NIOSH-0	Ca (National Institute for Occupational Safety and Health)	
13463-67	7-7 titanium dioxide	
14808-60	0-7 Quartz (SiO2)	
1333-86	6-4 Carbon black	
67-56	5-1 methanol	

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

bisphenolA(chloro)oxirane polymer	
Mercaptan I	Ferminated Polymer NJTS 800938 5952	
Cellulose		
POLYMER	OF EPICHLOROHYDRIN-POLYGLYCOL	
Hazard state	ements	
H315 Cause	s skin irritation.	
H319 Cause	s serious eye irritation.	
H317 May c	ause an allergic skin reaction.	
	cted of causing cancer.	
-	ause respiratory irritation.	
•	ry statements	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray	
P280	Wear protective gloves.	
P280	Wear eye protection / face protection.	
P264	Wash thoroughly after handling.	
P271	Use only outdoors or in a well-ventilated area.	
P272	Contaminated work clothing must not be allowed out of the workplace.	
		(Contd. on page 1



Page 10/10

Reviewed on 01/08/2016

Printing date 05/31/2016

Trade name: 39777 High-Build Self Leveling Seam Sealer

	(Contd. of page 9)
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P305+P351+P338	B If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P363	Wash contaminated clothing before reuse.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- Date of preparation / last revision 05/31/2016 / 5
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • * Data compared to the previous version altered.