SEM

Printing date 05/31/2016 Reviewed on 01/08/2016

1 Identification

· Product identifier

· Trade name: 39803 Clear Chip Guard

· Article number: 39803

· Application of the substance / the mixture Coating

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

IISA



Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 1)

· Hazard pictograms









GHS04

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

toluene

acetone

P321

butanone

Cellulose Acetate Butyrate

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P251	Do not pierce or burn, even after use.
D2.60	

Do not breathe dust/fume/gas/mist/vapors/spray. P260 P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves.

P280 Wear eye protection / face protection. Wash thoroughly after handling. P264

Use only outdoors or in a well-ventilated area. P271

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell. P308+P313 IF exposed or concerned: Get medical advice/attention. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P331 Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water. P302+P352

Take off contaminated clothing and wash it before reuse. P362+P364

Store locked up. P405

Protect from sunlight. Store in a well-ventilated place. P410+P403

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 3)



Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	components:	
108-88-3	toluene	30 - 40%
68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
67-64-1	acetone	13 - 30%
78-93 <i>-3</i>	butanone	5 - 7%
	2-(propyloxy)ethanol	1.5 - 5%
9004-36-8	Cellulose Acetate Butyrate	1.5 - 5%
	NJ TSRN: 8009285004 Polyester Plasticizer	1.5 - 5%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

US



Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)



Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 4)

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

BEI

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm

BEI

78-93-3 butanone

PEL Long-term value: 590 mg/m³, 200 ppm

REL Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

BEI

· Ingredients with biological limit values:

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L

Medium: urine

Time: end of shift

Parameter: Toluene

0.3 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 6)



Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 5)

78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Color: According to product specification

· Odor: Characteristic

(Contd. on page 7)

SEM

Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

	(Contd. of page
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C
Flash point:	-103 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	465 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
Vapor pressure at 20 °C:	233 hPa
Density at 20 °C:	$0.75288 \ g/cm^3$
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	·): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	86.3 %
VOC content:	65.6 %
	615.3 g/l / 5.13 lb/gl
Solids content:	13.7 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 8)



Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 7)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 1	· LD/LC50 values that are relevant for classification:		
108-88-3 to	oluene		
Oral	LD50	5000 mg/kg (rat)	
Dermal	LD50	12124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5320 mg/l (mouse)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

Carethogenic categories	
· IARC (International Agency for Research on Cancer)	
108-88-3 toluene	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	

12 Ecological information

None of the ingredients is listed.

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.



Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 8)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN proper shipping name DOT Aerosols, flammable 1950 Aerosols IMDG AEROSOLS IATA AEROSOLS, flammable Transport hazard class(es) DOT Class 2.1 Label 2.1 ADR Class 2.5F Gases Label 2.1 IMDG, IATA Class 2.1 IMDG, IATA Void Environmental hazards:	UN-Number DOT, ADR, IMDG, IATA	UN1950
ADT Aerosols, flammable 1950 Aerosols IMDG AEROSOLS IATA AEROSOLS, flammable Transport hazard class(es) DOT Class Label 2.1 ADR Class Label 2.1 IMDG, IATA Class Label 2.1 Packing group DOT, ADR, IMDG, IATA Environmental hazards:		
ADR 1950 Aerosols IMDG AEROSOLS IATA AEROSOLS, flammable Transport hazard class(es) DOT Class 2.1 Label 2.1 ADR Class 2 5F Gases Label 2.1 IMDG, IATA Class 2.1 Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:		Aerosols, flammable
IATA AEROSOLS, flammable Transport hazard class(es) DOT Class Label 2.1 ADR Class Label 2.5F Gases Label 2.1 IMDG, IATA Class Label 2.1 Packing group DOT, ADR, IMDG, IATA Environmental hazards:	ADR	1950 Aerosols
Transport hazard class(es) DOT Class 2.1 Label 2.1 ADR Class 2 5F Gases Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:		
Class Label 2.1 ADR Class 2.1 ADR Class 2.5F Gases Label 2.1 IMDG, IATA Class 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	IATA	AEROSOLS, flammable
Class 2.1 ADR Class 2 5F Gases Label 2.1 IMDG, IATA Class 2.1 IMDG, IATA Class 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	Transport hazard class(es)	
Label 2.1 ADR Class 2 5F Gases Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	DOT	
Label 2.1 ADR Class 2 5F Gases Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	A	
Label 2.1 ADR Class 2 5F Gases Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:		
Label 2.1 ADR Class 2 5F Gases Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	LEVARMATER CV2	
Label 2.1 ADR Class 2 5F Gases Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:		
Class 2 5F Gases Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	Class	
Class Label 2.1 IMDG, IATA Class Label 2.1 Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	Label	2.1
Class Label 2.1 IMDG, IATA Class Label 2.1 Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	ADR	
Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:		
Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:		
Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:		
Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	2	
Label 2.1 IMDG, IATA Class 2.1 Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:	Class	2 SF Gases
IMDG, IATA Class Label Packing group DOT, ADR, IMDG, IATA Environmental hazards:		
Class Label 2.1 Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:		Δ,1
Label 2.1 Packing group DOT, ADR, IMDG, IATA Environmental hazards: Void	IMDG, IATA	
Label 2.1 Packing group DOT, ADR, IMDG, IATA Environmental hazards: Void		
Label 2.1 Packing group DOT, ADR, IMDG, IATA Environmental hazards: Void		
Label 2.1 Packing group DOT, ADR, IMDG, IATA Environmental hazards: Void		
Label 2.1 Packing group Void DOT, ADR, IMDG, IATA Void Environmental hazards: Void	~	
Packing group DOT, ADR, IMDG, IATA Void Environmental hazards:		
DOT, ADR, IMDG, IATA Void Environmental hazards:	Label	2.1
DOT, ADR, IMDG, IATA Void Environmental hazards:	Packing group	
		Void
	Environmental hazards:	
Marine pollutant: No	Marine pollutant:	No
	Special precautions for user	Warning: Gases

SEM

Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

	(Contd. of page
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
<u> </u>	SW22 For AEROSOLS with a maximum capacity of 1 litr
	Category A. For AEROSOLS with a capacity above 1 litr
	Category B. For WASTE AEROSOLS: Category C, Clear of living
	quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litr
	Segregation as for class 9. Stow "separated from" class 1 except f
	division 1.4. For AEROSOLS with a capacity above 1 litr
	Segregation as for the appropriate subdivision of class 2. F
	WASTE AEROSOLS: Segregation as for the appropriate subdivisi
	of class 2.
Transport in bulk according to Anne.	x II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
Transport/Additional information: DOT	
•	On passenger aircraft/rail: 75 kg
DOT	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
DOT Quantity limitations	
DOT Quantity limitations ADR	
DOT Quantity limitations ADR	On cargo aircraft only: 150 kg
DOT	On cargo aircraft only: 150 kg Code: E0
DOT Quantity limitations ADR Excepted quantities (EQ)	On cargo aircraft only: 150 kg Code: E0
DOT Quantity limitations ADR Excepted quantities (EQ) IMDG	On cargo aircraft only: 150 kg Code: E0 Not permitted as Excepted Quantity
DOT Quantity limitations ADR Excepted quantities (EQ) IMDG Limited quantities (LQ)	On cargo aircraft only: 150 kg Code: E0 Not permitted as Excepted Quantity 1L

15 Regulatory information

9004-36-8 Cellulose Acetate Butyrate

- $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture}}$
- · Sara

A	
· Section 3.	55 (extremely hazardous substances):
None of th	ne ingredient is listed.
· Section 3.	13 (Specific toxic chemical listings):
108-88-3	toluene
	ACRYLIC RESIN
78-93-3	butanone
· TSCA (To	oxic Substances Control Act):
108-88-3	toluene
67-64-	l acetone
78-93-3	B butanone
2807-30-9	9 2-(propyloxy)ethanol

(Contd. on page 11)

Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 10)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

· Cancerogenity categories

· EPA (Environmental Protection Agency)			
108-88-3	toluene	II	
67-64-1	acetone	I	
78-93-3	butanone	I	
· TLV (Thi	· TLV (Threshold Limit Value established by ACGIH)		

· TLV (Threshold Limit	Value established by ACGIH)
------------------------	-----------------------------

,	<u> </u>	
108-88-3	toluene	A4
67-64-1	acetone	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS04

GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

toluene

acetone

butanone

Cellulose Acetate Butyrate

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P211 Do not spray on an open flame or other ignition source.

(Contd. on page 12)

SEM

Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 11) P280 Wear protective gloves. P280 Wear eye protection / face protection. P264 Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. P271 P201 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. P202 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P308+P313 IF exposed or concerned: Get medical advice/attention. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P314 Get medical advice/attention if you feel unwell. P331 Do NOT induce vomiting. P302+P352 IF ON SKIN: Wash with plenty of water. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up. P410+P403 Protect from sunlight. Store in a well-ventilated place. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. P403+P233 P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 05/31/2016 / 8
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

 $NFPA: National\ Fire\ Protection\ Association\ (USA)$

 $HMIS: \ Hazardous\ Materials\ Identification\ System\ (USA)$

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 13)

SEM

Printing date 05/31/2016 Reviewed on 01/08/2016

Trade name: 39803 Clear Chip Guard

(Contd. of page 12)

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

* * Data compared to the previous version altered.

USA