Printing date 11/14/2016



Reviewed on 11/14/2016

1 Identification

- · Product identifier
- · Trade name: 42254 Rockit Liner Black
- · Article number: 42254
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

• Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard statements

H225 Highly flammable liquid and vapor.

H361 Suspected of damaging fertility or the unborn child.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P280 Wear protective gloves / eye protection / face protection.
- P240 Ground/bond container and receiving equipment.
- P233 Keep container tightly closed.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P201 Obtain special instructions before use.

(Contd. on page 2)

USA



Reviewed on 11/14/2016

SEM

Trade name: 42254 Rockit Liner Black

(Contd. of page 1)

P202 P303+P361+P	Do not handle until all safety precautions have been read and understood. 2353 If on skin (or hair): Take off immediately all contaminated clothing. Rins- shower.	e skin with water/
P308+P313	<i>IF exposed or concerned: Get medical advice/attention.</i>	
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.	
P405	Store locked up.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P501	Dispose of contents/container in accordance with local/regional/natio regulations.	nal/international
· Classification s		
· NFPA ratings		
I I I I I I I I I I I I I I I I I I I	Health = 0 Fire = 3 Reactivity = 0 (scale 0 - 4)	
· IIIIII - Tutings	(scale 0 - 4)	
FIRE 3	Health = 0 Fire = 3 Reactivity = 0	
• Other hazards		
· Results of PBT	and vPvB assessment	
• PBT: Not appli	icable.	
• vPvB: Not appl	licable.	
3 Composition	/information on ingredients	
	acterization: Mixtures	
· Description:		
	sting of the following components.	
Weight percent	ages	
· Dangerous con	nponents:	
540-88-5 te	ert-butyl acetate	10 -13%
123-86-4 n	n-butyl acetate	5 - 7%

540-88-5	tert-butyl acetate	10 -13%
	n-butyl acetate	5 - 7%
110-43-0	heptan-2-one	1.5 - 5%
67-64-1		1.5 - 5%
1330-20-7		1.5 - 5%
		1.5 - 5%
112945-52-5	SILICA	1-1.5%
108-65-6	2-methoxy-1-methylethyl acetate	1-1.5%
108-88-3	toluene	<u>≤</u> 1%

4 First-aid measures

*

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

USA

Printing date 11/14/2016

Trade name: 42254 Rockit Liner Black

- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

· Handling:

- · Precautions for safe handling
- No special measures required.
- Open and handle receptacle with care.
- · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Page 3/12

Reviewed on 11/14/2016

(Contd. of page 2)



USA

Printing date 11/14/2016

Trade name: 42254 Rockit Liner Black

• *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

540-88-5 tert-butyl acetate PEL Long-term value: 950 mg/m³, 200 ppm REL Long-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 710 mg/m³, 150 ppm REL Short-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 720 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm PEL Long-term value: 455 mg/m³, 100 ppm REL Long-term value: 233 mg/m³, 50 ppm TV Long-term value: 2400 mg/m³, 100 ppm REL Long-term value: 230 mg/m³, 250 ppm REL Long-term value: 2400 mg/m³, 250 ppm REL Long-term value: 590 mg/m³, 250 ppm BI Short-term value: 455 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm		· 1	
RELLong-term value: 950 m/m³, 200 ppmTLVShort-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm123-86-4 n-butyl acetatePELLong-term value: 710 mg/m³, 150 ppmRELShort-term value: 710 mg/m³, 150 ppmRELShort-term value: 710 mg/m³, 150 ppmLong-term value: 710 mg/m³, 150 ppmLong-term value: 712 mg/m³, 150 ppmLong-term value: 712 mg/m³, 150 ppmLong-term value: 238 mg/m³, 50 ppm110-43-0 heptan-2-onePELLong-term value: 465 mg/m³, 100 ppmRELLong-term value: 233 mg/m³, 50 ppmC7-64-1 acctonePELLong-term value: 2400 mg/m³, 100 ppmRELLong-term value: 2400 mg/m³, 500 ppmC7-64-1 acctonePELLong-term value: 590 mg/m³, 250 ppmRELLong-term value: 1187 mg/m³, 500 ppmLong-term value: 590 mg/m³, 250 ppmRELLong-term value: 137 mg/m³, 500 ppmLong-term value: 138 mg/m³, 100 ppmRELLong-term value: 137 mg/m³, 500 ppmLong-term value: 594 mg/m³, 100 ppmRELShort-term value: 435 mg/m³, 100 ppmLong-term value: 434 mg/m³, 100 ppmBEIIO8-65-62-methoxy-1-methylethyl acetateWEELLong-term value:	540-8	88-5 tert-butyl acetate	
TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 123-86-4 n-buyl acetate PEL Long-term value: 710 mg/m³, 150 ppm Long-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 110-43-0 heptan-2-one PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 233 mg/m³, 50 ppm 67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 509 mg/m³, 250 ppm TLV Short-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 594 mg/m³, 500 ppm Long-term value: 594 mg/m³, 500 ppm Long-term value: 1187 mg/m³, 500 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 594 mg/m³, 100 ppm REL Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 651 mg/m³, 100 ppm Long-term value: 651 mg/m³, 100 ppm Long-term value: 50 ppm Lo	PEL	Long-term value: 950 mg/m ³ , 200 ppm	
Long-term value: 238 mg/m³, 50 pm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm TIV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm Long-term value: 238 mg/m³, 50 ppm 110-43-> heptan-2-one PEL Long-term value: 465 mg/m³, 100 ppm Rett REL Long-term value: 233 mg/m³, 50 ppm 67-64-1 acetone PEL Long-term value: 2400 mg/m³, 100 ppm REL Long-term value: 2400 mg/m³, 500 ppm Long-term value: 2400 mg/m³, 500 ppm Long-term value: 590 mg/m³, 500 ppm REL Long-term value: 500 mg/m³, 500 ppm Long-term value: 509 mg/m³, 500 ppm Long-term value: 594 mg/m³, 500 ppm Long-term value: 594 mg/m³, 500 ppm Long-term value: 594 mg/m³, 500 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 100 ppm Long-term value: 435 mg/m³,	REL	Long-term value: 950 mg/m ³ , 200 ppm	
123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 110-43-0 heptan-2-one PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 233 mg/m³, 50 ppm 67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 250 ppm TLV Short-term value: 590 mg/m³, 250 ppm PEL Long-term value: 590 mg/m³, 250 ppm BEI Bei B I330-20-7 xylene PEL PEL Long-term value: 435 mg/m³, 100 ppm Long-term value: 559 mg/m³, 150 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 655 mg/m³, 100 ppm Long-term value: 655 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 100 ppm Long-term value: 655 mg/m³, 100 ppm Long-term value: 655 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm	TLV	Short-term value: 712 mg/m³, 150 ppm	
PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 50 ppm III0-43-0 heptan-2-one PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 233 mg/m³, 50 ppm TLV Long-term value: 2400 mg/m³, 100 ppm REL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 250 ppm TLV Short-term value: 590 mg/m³, 250 ppm PEL Long-term value: 590 mg/m³, 250 ppm REL Long-term value: 594 mg/m³, 500 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm Long-term value: 434 mg/m³, 100 ppm BEI II08-65-6 2-methoxy-1-methylethyl acetate WEEL		Long-term value: 238 mg/m ³ , 50 ppm	
REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm 110-43-oheptan-2-one PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 233 mg/m³, 50 ppm 67-64-1 Long-term value: 233 mg/m³, 50 ppm 67-64-1 Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 500 ppm Long-term value: 590 mg/m³, 250 ppm Long-term value: 590 mg/m³, 500 ppm REL Long-term value: 590 mg/m³, 500 ppm Long-term value: 590 mg/m³, 500 ppm Long-term value: 590 mg/m³, 500 ppm BEI Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 651 mg/m³, 100 ppm Long-term value: 434 mg/m³, 100 ppm BEI 108-65-5 2-methoxy-1-methylethyl acetate Long-term value: 50 ppm IO8-88-3 toluem Eeling limit value: 500 ppm FEL Long-term value: 200 ppm	123-8	86-4 n-butyl acetate	
Long-term value: 710 mg/m³, 150 ppmTLVShort-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm110-43-Jeptan-2-onePELLong-term value: 465 mg/m³, 100 ppmRELLong-term value: 465 mg/m³, 100 ppmTLVLong-term value: 233 mg/m³, 50 ppm67-64-JacceonePELLong-term value: 2400 mg/m³, 1000 ppmRELLong-term value: 2400 mg/m³, 1000 ppmRELLong-term value: 2400 mg/m³, 1000 ppmRELLong-term value: 500 mg/m³, 250 ppmBEJLong-term value: 590 mg/m³, 500 ppmBEJLong-term value: 594 mg/m³, 500 ppmBEJLong-term value: 650 mg/m³, 100 ppmRELShort-term value: 1187 mg/m³, 500 ppmLong-term value: 590 mg/m³, 500 ppmBEJShort-term value: 655 mg/m³, 100 ppmBEJLong-term value: 435 mg/m³, 100 ppmRELShort-term value: 655 mg/m³, 150 ppmLong-term value: 655 mg/m³, 150 ppmLong-term value: 655 mg/m³, 150 ppmBEJEIIONG-term value: 434 mg/m³, 100 ppmBEJIONG-term value: 50 ppmIONG-term value: 50 ppmIONG-term value: 200 ppmPELLong-term value: 200 ppmCelling limit value: 200 ppmCelling limit value: 300, 500* ppm*10-min peak per 8-hr shift	PEL	Long-term value: 710 mg/m ³ , 150 ppm	
TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 110-43-0 heptan-2-one PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 465 mg/m³, 100 ppm TLV Long-term value: 233 mg/m³, 50 ppm 67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 500 ppm Long-term value: 594 mg/m³, 500 ppm Long-term value: 594 mg/m³, 500 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm BEI Iong-term value: 434 mg/m³, 100 ppm BEI Iong-term value: 434 mg/m³, 100 ppm BEI Iong-term value: 434 mg/m³, 100 ppm BEI Iong-term value: 300 ppm Cong-term value: 434 mg/m³, 100 ppm <	REL		
Long-term value: 238 mg/m³, 50 ppm 110-43-0 heptan-2-one PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 465 mg/m³, 100 ppm TLV Long-term value: 233 mg/m³, 50 ppm 67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI 1330-2v-7 xylene Deg-term value: 594 mg/m³, 100 ppm PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 100 ppm BEI Short-term value: 651 mg/m³, 100 ppm BEI Long-term value: 434 mg/m³, 100 ppm BEI Short-term value: 651 mg/m³, 100 ppm BEI Short-term value: 651 mg/m³, 100 ppm BEI Cong-term value: 434 mg/m³, 100 ppm BEI Cong-term value: 300 ppm Ceiling linin v			
III-0-13 III-0-13 PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 233 mg/m³, 50 ppm 67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 2400 mg/m³, 250 ppm TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI 108-65-6 2-methoxy-1-methylethyl acetate WEEL Long-term value: 50 ppm LORs-88-3 toluene PEL PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	TLV		
PELLong-term value: 465 mg/m³, 100 ppmRELLong-term value: 465 mg/m³, 100 ppmTLVLong-term value: 233 mg/m³, 50 ppm67-64-I acetonePELLong-term value: 2400 mg/m³, 1000 ppmRELLong-term value: 590 mg/m³, 250 ppmTLVShort-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppmT330-20-7 xylenePELLong-term value: 435 mg/m³, 100 ppm BEIRELShort-term value: 435 mg/m³, 100 ppm BEITIVShort-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppmRELShort-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppmTLVShort-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppmBEI108-65-6 2-methoxy-1-methylethyl acetateWEELLong-term value: 50 ppmID8-88-3 toluenePELPELLong-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift		· · · · · ·	
REL Long-term value: 465 mg/m³, 100 ppm TVV Long-term value: 233 mg/m³, 50 ppm 67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 290 mg/m³, 250 ppm Ding-term value: 1187 mg/m³, 500 ppm Long-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI 1330-20-7 xylene PEL Long-term value: 555 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm BEI 108-65-6 2-methoxy-1-methylethyl acetate WEEL Long-term value: 50 ppm BEI 108-83-3 toluene PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift			
TLVLong-term value: 233 mg/m³, 50 ppm67-64-IacetonePELLong-term value: 2400 mg/m³, 1000 ppmRELLong-term value: 590 mg/m³, 250 ppmTLVShort-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppmBEI1330-20-7 xylenePELLong-term value: 435 mg/m³, 100 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppmRELShort-term value: 435 mg/m³, 100 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppmTLVShort-term value: 651 mg/m³, 100 ppm BEI108-65-6 2-methoxy-1-methylethyl acetateWEELLong-term value: 50 ppm Long-term value: 50 ppm BEIPELLong-term value: 50 ppm Long-term value: 50 ppm BEI108-88-3 toluenePELLong-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift			
67-64-J acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm JIV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm BEI 108-65-6 Userstein value: 434 mg/m³, 100 ppm BEI 108-65-6 Userstein value: 50 ppm BEI 108-85-5 Long-term value: 50 ppm BEI PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift		· · · · · ·	
PELLong-term value: 2400 mg/m³, 1000 ppmRELLong-term value: 590 mg/m³, 250 ppmTIVShort-term value: 1187 mg/m³, 500 ppmLong-term value: 594 mg/m³, 250 ppmBEI1330-2-7 xylenePELLong-term value: 435 mg/m³, 100 ppmRELShort-term value: 435 mg/m³, 100 ppmRELShort-term value: 655 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmTIVShort-term value: 651 mg/m³, 100 ppmDistributionShort-term value: 435 mg/m³, 100 ppmBEI108-65-6Demthylethyl acetateWEELLong-term value: 50 ppm108-88-3FeLLong-term value: 200 ppmCeiling limit value: 300; 500* ppm*10-min peak per 8-hr shift			
RELLong-term value: 590 mg/m³, 250 ppmTLVShort-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI1330-2	67-64		
TLVShort-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI1330-2-0-7 xylenePELLong-term value: 435 mg/m³, 100 ppmRELShort-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppmTLVShort-term value: 651 mg/m³, 100 ppm BEI108-65-6 2-methoxy-1-methylethyl acetateWEELLong-term value: 50 ppm108-88-3 toluenePELLong-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	PEL	Long-term value: 2400 mg/m³, 1000 ppm	
Long-term value: 594 mg/m³, 250 ppm BEI1330-20-7 xylenePELLong-term value: 435 mg/m³, 100 ppm RELShort-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppmTLVShort-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI108-65-6 2-methoxy-1-methylethyl acetateWEELLong-term value: 50 ppm108-88-3 toluenePELLong-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	REL	Long-term value: 590 mg/m ³ , 250 ppm	
BEI 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI 108-65-6 2-methoxy-1-methylethyl acetate WEEL Long-term value: 50 ppm 108-88-3 toluene PEL Long-term value: 200 ppm *10-min peak per 8-hr shift	TLV		
1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI 108-65-5 2-methoxy-1-methylethyl acetate WEEL Long-term value: 50 ppm 108-88-3 toluene PEL Long-term value: 200 ppm *10-min peak per 8-hr shift			
PELLong-term value: 435 mg/m³, 100 ppmRELShort-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppmTLVShort-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI108-65-6 2-methoxy-1-methylethyl acetateWEELLong-term value: 50 ppm108-88-3 toluenePELLong-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	1220		
RELShort-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppmTLVShort-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI108-65-6 2-methoxy-1-methylethyl acetateWEELLong-term value: 50 ppm108-88-3 toluenePELLong-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift		•	
Long-term value: 435 mg/m³, 100 ppmTLVShort-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI108-65-6 2-methoxy-1-methylethyl acetateWEELLong-term value: 50 ppm108-88-3 toluenePELLong-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift			
TLVShort-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI108-65-6 2-methoxy-1-methylethyl acetateWEELLong-term value: 50 ppm108-88-3 toluenePELLong-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	REL		
Long-term value: 434 mg/m ³ , 100 ppm BEI 108-65-6 2-methoxy-1-methylethyl acetate WEEL Long-term value: 50 ppm 108-88-3 toluene PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	TIV	· · · · · ·	
BEI 108-65-6 2-methoxy-1-methylethyl acetate WEEL Long-term value: 50 ppm 108-88-3 toluene PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	ILV		
WEEL Long-term value: 50 ppm 108-88-3 toluene PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift			
108-88-3 toluene PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	108-6	65-6 2-methoxy-1-methylethyl acetate	
PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	WEEI	L Long-term value: 50 ppm	
Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	108-8	88-3 toluene	
*10-min peak per 8-hr shift	PEL		
	-		

Reviewed on 11/14/2016

(Contd. of page 3)




SEM Reviewed on 11/14/2016

Page 5/12

Trade name: 42254 Rockit Liner Black

REL	(Contd. of page Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI
· Ingr	edients with biological limit values:
	4-1 acetone
BEI	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)
	0-20-7 xylene
BEI	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
400	Parameter: Methylhippuric acids
	88-3 toluene
BEI	0.02 mg/L
	Medium: blood
	Time: prior to last shift of workweek
	Parameter: Toluene
	0.03 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Toluene
	0.3 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: o-Cresol with hydrolysis (background)
·Add	itional information: The lists that were valid during the creation were used as basis.
·Exn	osure controls
	onal protective equipment:
	eral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
Was	h hands before breaks and at the end of work.
Stor	e protective clothing separately.
	thing equipment: Not required.
	ection of hands:
	to missing tests no recommendation to the glove material can be given for the product/ the preparation/ t
	nical mixture.
Sele	ction of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	m la construction de la construc
1/1	Protective gloves
Thc	-
ine	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. (Contd. on page



SEM

Reviewed on 11/14/2016

Trade name: 42254 Rockit Liner Black

· Material of gloves

(Contd. of page 5)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information Appearance:	
Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	97 °C
Flash point:	15 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	2.6 Vol %
Upper:	13.0 Vol %
Vapor pressure at 20 °C:	41 hPa
Density at 20 °C:	1.22097 g/cm ³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

USA

Printing date 11/14/2016

Reviewed on 11/14/2016

Trade name: 42254 Rockit Liner Black

		(Contd. of page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	37.3 %	
VOC content:	16.6 %	
	224.8 g/l / 1.88 lb/gl	
Solids content:	62.5 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information


- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

•	Carcino	genic	categories
	can conto	201000	caregories

· IARC (Inte	rnational Agency for Research on Cancer)	
1330-20-7	xylene	3
1333-86-4	Carbon black	2B
108-88-3	toluene	3
111-76-2	2-butoxyethanol	3
· NTP (Natio	onal Toxicology Program)	
None of the	ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	ingredients is listed.	
		118

(Contd. on page 8)





Reviewed on 11/14/2016

Trade name: 42254 Rockit Liner Black

(Contd. of page 7)

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, IMDG, IATA	UN1263	
· UN proper shipping name		
$\cdot DOT$	Paint	
· ADR	1263 Paint, special provision 640D	
· IMDG, IATA	PAINT	
· Transport hazard class(es)		
·DOT		
A		
PLANASHE F 1000		
•		
· Class	3 Flammable liquids	
· Label	3	

Printing date 11/14/2016

Reviewed on 11/14/2016

SEM

Trade name: 42254 Rockit Liner Black

	(Contd. of pag
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
ÊMS Number:	<i>F-E</i> , <u><i>S</i>-<i>E</i></u>
Stowage Category	В
Transport in bulk according to Annex II MARPOL73/78 and the IBC Code	of Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
~ '	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

*

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

 • Section 355 (extremely hazardous substances):

 None of the ingredient is listed.

 • Section 313 (Specific toxic chemical listings):

 Acrylic Resin

 1330-20-7
 xylene

 108-88-3
 toluene

 111-76-2
 2-butoxyethanol



Page 10/12

Reviewed on 11/14/2016

Printing date 11/14/2016

Trade name: 42254 Rockit Liner Black

TSCA (To	xic Substances Control Act):	
	tert-butyl acetate	
	<i>n-butyl acetate</i>	
	h-buly accure	
	acetone	
1330-20-7		
	4-chloro-alpha,alpha,alpha-trifluorotoluene	
	2-methoxy-1-methylethyl acetate	
	Carbon black	
	toluene	
	7 dibutyltin dilaurate	
	2 2-butoxyethanol	
	OXIRANE, ME, POLYMER	
Propositio		
-		
	s known to cause cancer:	
1330-20-7		
	Carbon black	
<i>C</i> 1 · 1	s known to cause reproductive toxicity for females:	
	ne ingredients is listed.	
None of th		
None of the Chemical	ne ingredients is listed.	
None of th Chemical None of th	ne ingredients is listed. s known to cause reproductive toxicity for males:	
None of th Chemical None of th	ne ingredients is listed. s known to cause reproductive toxicity for males: the ingredients is listed. s known to cause developmental toxicity:	
None of th Chemical None of th Chemical 108-88-3	ne ingredients is listed. s known to cause reproductive toxicity for males: the ingredients is listed. s known to cause developmental toxicity: toluene	
None of the Chemical None of the Chemical 108-88-3 Cancerog	the ingredients is listed. s known to cause reproductive toxicity for males: the ingredients is listed. s known to cause developmental toxicity: toluene enity categories	
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env	ne ingredients is listed. s known to cause reproductive toxicity for males: the ingredients is listed. s known to cause developmental toxicity: toluene	
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Enw 67-64-1	the ingredients is listed. s known to cause reproductive toxicity for males: the ingredients is listed. s known to cause developmental toxicity: toluene enity categories pironmental Protection Agency) acetone	
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7	the ingredients is listed. s known to cause reproductive toxicity for males: the ingredients is listed. s known to cause developmental toxicity: toluene enity categories pironmental Protection Agency) acetone	Ι
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-3	<pre>he ingredients is listed. s known to cause reproductive toxicity for males: he ingredients is listed. s known to cause developmental toxicity: toluene enity categories rironmental Protection Agency) acetone xylene toluene</pre>	I
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-3 111-76-2	<pre>he ingredients is listed. s known to cause reproductive toxicity for males: he ingredients is listed. s known to cause developmental toxicity: toluene enity categories rironmental Protection Agency) acetone xylene toluene 2-butoxyethanol</pre>	І І.
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-3 111-76-2 TLV (Thr	<pre>he ingredients is listed. s known to cause reproductive toxicity for males: he ingredients is listed. s known to cause developmental toxicity: toluene enity categories itronmental Protection Agency) acetone toluene toluene 2 2-butoxyethanol eshold Limit Value established by ACGIH)</pre>	I I N
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-5 111-76-2 TLV (Thr 67-64-1	<pre>ke ingredients is listed. ke known to cause developmental toxicity: toluene enity categories ironmental Protection Agency) acetone acetone toluene 2-butoxyethanol eshold Limit Value established by ACGIH) acetone</pre>	
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-3 111-76-2 TLV (Thr 67-64-1 1330-20-7	<pre>ke ingredients is listed. ke ingredient</pre>	I I N N A A
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-3 111-76-2 TLV (Thr 67-64-1 1330-20-7 1333-86-4	are ingredients is listed. sknown to cause reproductive toxicity for males: are ingredients is listed. sknown to cause developmental toxicity: toluene enity categories eritronmental Protection Agency) acetone toluene 2-butoxyethanol eshold Limit Value established by ACGIH) acetone xylene categone xylene categone zylene categone zotone xylene acetone xylene categone zotone xylene acetone xylene	I I N N N N N N N N N N
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-3 111-76-2 TLV (Thr 67-64-1 1330-20-7 1333-86-4 108-88-3	the ingredients is listed. s known to cause reproductive toxicity for males: the ingredients is listed. s known to cause developmental toxicity: toluene enity categories trironmental Protection Agency) acetone xylene 2-butoxyethanol eshold Limit Value established by ACGIH) acetone xylene Carbon black toluene	I I N N N N N N N N N N
None of the Chemical None of the Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-3 111-76-2 TLV (Thr 67-64-1 1333-86-4 108-88-3 77-58-7	<pre>ke ingredients is listed. ke ingredient</pre>	I I N N N N N N N N N N
None of th Chemical None of th Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-3 111-76-2 TLV (Thr 67-64-1 1330-20-7 1333-86-4 108-88-3 77-58-7 111-76-2	<pre>ke ingredients is listed. ke known to cause developmental toxicity: toluene enity categories enity categories</pre>	I I N N N N N N N N N N
None of the Chemical None of the Chemical 108-88-3 Cancerog EPA (Env 67-64-1 1330-20-7 108-88-3 111-76-2 TLV (Thr 67-64-1 1333-80-4 108-88-3 77-58-7 111-76-2 NIOSH-C	<pre>ke ingredients is listed. ke ingredient</pre>	I I I Л Л Л Л Л Л Л Л Л Л

Printing date 11/14/2016

Safety Data Sheet acc. to OSHA HCS



Page 11/12

Reviewed on 11/14/2016

Trade name: 42254 Rockit Liner Black

	(Contd. of page 10
Hazard pictogra	ams
JAK J	
GHS02 GHS	508
Signal word Da	nger
Hazard stateme	
H225 Highly fla	mmable liquid and vapor.
0 . 0	of damaging fertility or the unborn child.
Precautionary s	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P280	Wear protective gloves / eye protection / face protection.
P240	Ground/bond container and receiving equipment.
P233	Keep container tightly closed.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P303+P361+P3	353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water
	shower.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P405	Store locked up.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations. • assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

- *Contact: Steve Gaver (sgaver@semproducts.com)*
- Date of preparation / last revision 11/14/2016 / 7
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)
- *PBT: Persistent, Bioaccumulative and Toxic*

(Contd. on page 12)

USA

Printing date 11/14/2016

Reviewed on 11/14/2016

EN

Trade name: 42254 Rockit Liner Black

(Contd. of page 11)

Page 12/12

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Repr. 2: Reproductive toxicity – Category 2 • * Data compared to the previous version altered.

USA