

PRODUCT: 440Express™ Micro-Pinhole Eliminator

PART

NUMBER:	100440	16 fl. oz.	6 units per case	8 lbs. per case
	100444	4 fl. oz. Kit	1 unit per case	2 lbs. per case
	100439	12 pack	6 units per case	5 lbs. per case

DESCRIPTION: 440Express Micro-Pinhole Eliminator is a quick fix for micro-pinholes that are hard to identify prior to primer application. This 1K patent-pending technology is a high-solids polyester that is easy to apply and quick to dry. Testing has shown, when used properly, 440Express will eliminate up to 90% of all rework caused by micro-pinholes. **440Express should be applied with part #439 Applicators. 440Express is not designed to replace polyester glazing putties.**

APPROVED SUBSTRATES:

- **Cured and sanded Evercoat 2K pourable glazing putties**
 - 410 Glaze-It®
 - 413/414 Metal Glaze® OEM™
 - 415/416 Metal Glaze®
 - 417 Glaze Coat
 - 420/421 Easy Sand™
- **Cured and sanded Quantum1™ 10:1 Single Step Repair Technology**
- **Not recommended for use over conventional Body Filler or Primer Surfacer.**

PREPARATION:



- Finish your dent repair process by sanding with 180-grit or finer sandpaper.
- Remove dust with compressed air.

APPLICATION:



- Shake 440Express and apply a small amount of 440Express on the applicator sponge or the repair area.
- Wipe 440Express over the entire repair area. Multiple applications may be necessary on larger repair areas.
- Continue to wipe until a light coat of 440Express has been applied. When 440Express is applied properly, the repair area will still be visible through the light coat. Micro-pinholes will be easy to identify.
- Allow to dry 15 minutes and apply a primer surfacer according to paint manufacturer's recommendations.

NOTE: If excess 440Express builds up on the repair area, allow to dry 15 minutes, then lightly sand using 400-500 grit sandpaper prior to applying primer. Excess film build will be noticeably darker than recommended application of 440Express.

SAFETY & HANDLING:

Read all directions and warnings prior to using Evercoat products. Material Safety Data Sheets can be found online at www.evercoat.com.

NOTES:

440Express is not designed to replace polyester glazing putties. This product is designed to fix micro pin-holes before going to primer surfacer.