



AEROPRO 2K Acid Etch Primer

Description: **AeroPro Acid Etch** is a 2K ready to use etch primer available in 15.35oz aerosol. It is used for priming bare metal surfaces, this promotes adhesion of paint and prevents steel from rusting.

Acid Etch is chromate free. Typical applications are over rub through areas prior to painting, on new bare metal panels or over bare seams before sealant is applied.

Surface preparation and instructions for use:

Acid Etch can be applied to the following surfaces:-

- Bare steel.
- Aluminium.
- Galvanized and Zinc coated steels.
- Fully cured paint.
- Polyester bodyfillers and G.R.P.

Thoroughly clean and degrease surfaces with #5960 Final Wipe or a VOC Compliant Wax & Grease Remover. Abrade wet or dry with 280-320 abrasive. Re-clean, dry and degrease.

Application:

Shake can thoroughly before use for a minimum of 2 minutes. Apply 1-2 light even coats. Allow 3-5 minutes flash off time between coats.

Dry Time:

Allow 10-20 minutes before overcoating. Drying time is dependent upon film thickness, humidity and temperature.

Over-Painting:

Under normal circumstances it is not necessary to flat **Acid Etch** and should be directly overcoated. **Acid Etch** may be overcoated directly with top coat. However, if the repair requires additional build primer filler should be used before topcoat is applied.

Product Part No: **AeroPro Acid Etch #5975**- 15.35oz aerosol

Visit our website for more information: www.autobodybrands.com