Printing date 05/31/2016 Reviewed on 05/17/2016

1 Identification

- · Product identifier
- · Trade name: 68442 Mini-Max Clear Fast Set Adhesive
- · Article number: 68442
- · Application of the substance / the mixture Adhesives
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

GHS06

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: POLYAMINE POLYMERCAPTAN EPOXY HARDENER BISPHENOL F EPOXY RESIN

(Contd. on page 2)

acc. to OSHA HCS



Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 1)

TERTIARY AMINE

BISPHENOL A EPOXY RESIN

· Hazard statements

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P260 Do not breathe dusts or mists.

P280 Wear protective gloves / protective clothing. P280 Wear eye protection / face protection.

P264 Wash thoroughly after handling.

Do not eat, drink or smoke when using this product. P270 P271 Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace. P272

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

If skin irritation or rash occurs: Get medical advice/attention. P333+P313

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.



Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:				
	POLYAMINE POLYMERCAPTAN EPOXY HARDENER	40 - 60%		
28064-14-4	BISPHENOL F EPOXY RESIN	30 - 40%		
25085-99-8	BISPHENOL A EPOXY RESIN	10 -13%		
	TERTIARY AMINE	1.5 - 5%		

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

SEM

Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 3)

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- Storage.
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

acc. to OSHA HCS

Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

. 1	njormation on vasic p	pnysicai ana	cnemicai	properues
. (General Information			

· Appearance:

Form: Liquid

Color: According to product specification

· Odor: Characteristic · Odor threshold: Not determined. · pH-value: Not determined.

· Change in condition

Undetermined. *Melting point/Melting range:* Boiling point/Boiling range: Undetermined.

· Flash point: 94 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Not determined. Decomposition temperature:

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard. In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower: Not determined. Not determined. Upper:

Not determined. · Vapor pressure:

· Density at 20 °C: 1.13348 g/cm³

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

SEM

Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

		(Contd. of page
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

 ${\it The product shows the following dangers according to internally approved calculation methods for preparations:}$

Toxic

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

64-17-5 ethanol

(Contd. on page 7)



Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN2923
· UN proper shipping name	
· DOT	Corrosive solids, toxic, n.o.s. (POLYAMINE POLYMERCAPTA EPOXY HARDENER, [3-(2,3-epoxypropoxy)propyl trimethoxysilane)
· ADR	2923 Corrosive solids, toxic, n.o.s. (POLYAMIN POLYMERCAPTAN EPOXY HARDENER, [3-(2,3-epoxypropox propyl]trimethoxysilane)
· IMDG, IATA	CORROSIVE SOLID, TOXIC, N.O.S. (POLYAMIN POLYMERCAPTAN EPOXY HARDENER, [3-(2,3-epoxypropox propyl]trimethoxysilane)

(Contd. on page 8)

SEM

Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 7) · Transport hazard class(es) $\cdot DOT$ · Class 8 Corrosive substances · Label 8, 6.1 $\cdot ADR$ · Class 8 Corrosive substances · Label 8+6.1 · IMDG 8 Corrosive substances · Class · Label 8/6.1 \cdot IATA · Class 8 Corrosive substances · Label 8 (6.1) · Packing group · DOT, ADR, IMDG, IATA Ш · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Corrosive substances F-A,S-B· EMS Number: · Segregation groups Alkalis · Stowage Category · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ On passenger aircraft/rail: 25 kg · Quantity limitations

On cargo aircraft only: 100 kg

(Contd. on page 9)

Safety Data Sheet acc. to OSHA HCS

SEM

Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 8
ORM-D 49CFR 173-150,156,306
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
5 kg
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
UN 2923 CORROSIVE SOLIDS, TOXIC, N.O.S. (POLYAMINI
POLYMERCAPTAN EPOXY HARDENER, [3-(2,3)
EPOXYPROPOXY)PROPYL]TRIMETHOXYSILANE), 8 (6.1), III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

67-56-1 methanol

· TSCA (Toxic Substances Control Act):

28064-14-4 BISPHENOL F EPOXY RESIN

25085-99-8 BISPHENOL A EPOXY RESIN

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

919-30-2 3-aminopropyltriethoxysilane

67-56-1 methanol

64-17-5 ethanol

- · Proposition 65
- · Chemicals known to cause cancer:

28064-14-4 BISPHENOL F EPOXY RESIN

25085-99-8 BISPHENOL A EPOXY RESIN

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

64-17-5 ethanol

(Contd. on page 10)

USA



Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 9)

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

64-17-5 ethanol *A3*

· NIOSH-Ca (National Institute for Occupational Safety and Health)

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

GHS06 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

POLYAMINE POLYMERCAPTAN EPOXY HARDENER

BISPHENOL F EPOXY RESIN

TERTIARY AMINE

BISPHENOL A EPOXY RESIN

· Hazard statements

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P260 Do not breathe dusts or mists.

P280 Wear protective gloves / protective clothing. P280 Wear eye protection / face protection. P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace. P272

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

(Contd. on page 11)

Safety Data Sheet acc. to OSHA HCS

SEM

Printing date 05/31/2016 Reviewed on 05/17/2016

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 05/31/2016 / 7
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

-USA