


PRODUCT FEATURES & APPLICATION



Dry 2 hours +or-
Also wet on wet
Paintable 30 minutes**



Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

EURO GRAVEL GUARD

TEL (905) 670-5411

FAX (905) 670-5174

Stock Number BVGEB, BLACK Part Number 9120 (1 Liter) BVGE25 Part# 912025 (25 liter)
Stock Number BVGEW WHITE Part Number 9121 (1 Liter) BVGE3-25 Part# 912125 (25 Liter)
Size: 1 Liter European Style Can and 5 Liter Cans.

Description:

Euro Gravel Guard is an paintable VERY HIGH solid anti gravel, anti corrosion coating with excellent sound deadening properties. Euro Gravel Guard is formulated from synthetic resins. The product after drying may also be sanded.

Features:

- Can be painted wet on wet
- A very high build coating.
- Many many uses.

Surface Preparation:

1. Surfaces must be clean and dry.
2. Clean surface with a some fast drying solvent. We strongly recommend Sure Solv Part # BSS (10058). Finish by sanding then clean again and allow to dry.
3. For applying on aluminum our Super Acid Etch product SEPA (24010) is highly recommended.
4. Euro Gravel Guard is high build and ready for use however if you want to vary the texture, you may wish to reduce it with up to 5% of cellulose thinners.
5. Cellulose thinners may also be used to clean the BUPE gun.

Application Instructions:

1. Shake the can well.
2. Attach the BUPAE gun to the Euro Gravel Guard can.
3. Allow 10-15 minutes between coats to let the solvent flash off.
4. One coat will give you between 100-150 microns at a pressure of 43-72 PSI. Spray distance should be 30cm or 12 inches.
5. More or less pressure will give a flatter textured look. Also the BUPE gun has the advantage of being able to vary the texture by adjusting the pressure nozzle feature on the gun.
6. Dry time is about 2 hours at 70f or 30 minutes in the bake oven at low bake (60c). Euro Gravel Guard can also be painted wet on wet within 30 minutes with 2K paints.
7. The use of a U.V. clear coat is recommended for high gloss and protection from fading.

Note: Avoid applying any materials on or near catalytic converters, mufflers due to extreme heat.

In the event the MSDS (Material Safety Data Sheet) on this product is not in your files, you can request one from Dominion Sure Seal Regulatory Compliance at 1800 265-0790, ext. MSDS.



Dry time 2 hours +or- Paintable in 30 minutes**
Also wet on wet

EURO GRAVEL GUARD

Stock Number BVGE, Part Number # 3010 (1 Liter) BLACK
Stock Number BVGE3 (White)

Size: 1 Liter European Style Can 5 Liter Cans.

TECHNICAL SPECIFICATIONS

Consistence;	Liquid with good sag resistance
Colour:	Black, Gray and White
Viscosity (20c, 72f):	Brookfield (after 2 min mixing) 12-160 Pas (spindle 5/V1/2)
Density (20c, 72f):	DIN51757 1.23-1.27 Kg.ltr
Solid Content:	Sartorious 56.0-60%

PROPERTIES

Dry to touch;	At+-20C 65%RH 15-30 mins (+-600mu)
Completely dry:	At+-20C 65%RH 60-90 hours (+-600mu)
	At 60C (<u>oven</u>) 20-30 minutes (+-600mu)
	At 60C (Infra Red) 20-30 minutes (+-600mu)

Paintable @+- 20C 65%RH:

2K Acrylic System After 30 minutes (wet on wet)
Basecoat system After 30 minutes (wet on wet)
Waterbase system Possible after FULL drying
Brookfield (after 2 min mixing) 120-160 Pas (Spindle 5/V1/2)

Colour:	Waterbase system Possible after FULL drying
Viscosity (20c, 72f):	Brookfield (after 2 min mixing) 120-160 Pas (Spindle 5/V1/2)
Chemical resistance:	Hardened against water, saltspray, oil, soft acids and bases
Temperature resistance:	Hardened against -25C - +80C
Usage:	With +- mu wet layer +-0.8kg/m2 +-0.6 ltr/m2
Non reversible:	With solvents
Cleaning:	Fresh material solvents by hand

Visit our web site at www.dominionsureseal.com or phone 1-800 265 0790 for more information