

FR Series Filter-Regulators



FR250-G



FR500-G

Filter-Regulators

- Filter with adjustable 0-120 PSI regulator
- Filter/Regulator with glass face chrome gauge
- Low pressure drop
- Can be wall mounted or panel nut mounted
- Low cost, high efficiency design
- Semi-automatic drain with manual override
- Filters to 5 micron
- Maximum pressure is 230 PSI
- Temperature range from 40°F to 120°F

	Port Size (in)	Flow Capacity (scfm)	Filter Capacity	Height (in)	Depth (in)	Width (in)
FR250-G	1/4"	30	5 micron+	7.8	1.65	1.65
FR380-G	3/8"	80	5 micron +	10.8	2.49	2.49
FR500-G	1/2"	80	5 micron+	10.8	2.49	2.49

FR250-G

Replacement Element: FR250-E
 Replacement Bowl Assy: F250-BMD
 Replacement O-ring: F250-OR
 Optional Bracket: F250-BKT
 Pressure Gauge: PG-160-1.5-CB

FR380-G

Replacement Element: FR380-E
 Replacement Bowl Assy: F380-BMD
 Replacement O-ring: F380-OR
 Optional Bracket: F380-BKT
 Pressure Gauge: PG-160-1.5-CB

FR500-G

Replacement Element: FR500-E
 Replacement Bowl Assy: F500-BMD
 Replacement O-ring: F500-OR
 Optional Bracket: F500-BKT
 Pressure Gauge: PG-160-1.5-CB