

Revision date : 2014/12/12 Page: 1/11 Version: 3.0 (30090849/CDU GEN US/EN)

1. Substance/preparation and company identification

Company **BASE CORPORATION** 100 Park Avenue Florham Park, NJ 07932, USA 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

unborn child

3 Vapours ma

nervous system

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin corrosion/irritation

Reproductive toxicity Specific target organ toxicity - single exposure

cause drowsiness and dizziness. Specific target organ toxicity - repeated exposu 2 Central

Flammable liquids Hazardous to the aquatic environment - acute

Label elements

Pictogram: Flame

Exclamation mark Health hazard

Signal Word:

Danger

Hazard Statement:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness. H361 Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged

or repeated exposure.

Safety data sheet LR11 LIMCO FAST REDUCER Revision date: 2014/12/12

Revision date : 2014/12/12 Page: 2/11 Version: 3.0 (30090849/CDU_GEN_US/EN)

Precautionary P201 P261	Stateme	ents (Prevention): Obtain special instructions before use. Avoid breathing
P260 P202		dust/fume/gas/mist/vapours/spray. Do not breathe dust or mist. Do not handle until all safety precautions have been read and understood. Ground/bond container and receiving equipment.
P240		
P233 P243		Keep container tightly closed. Take precautionary measures against static
D0.41		discharge.
P241		Use explosion-proof electrical/ventilating/lighting/equipment.
P242 P281		Use only non-sparking tools. Use personal protective equipment as
P201		required.
P264		Wash with plenty of water and soap thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
P210		
P271		
P280		
Precautionary P314	Statements (Response): Get medical advice/attention if you feel	
P308 + P313		unwell. IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing and wash before reuse. In case of fire: Use water spray for extinction. IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell.
P304 + P340		
P303 + P361 +	P353	
P332 + P313		
P321 P362 + P364		
P370 + P378		
P302 + P352		
P312		
Precautionary P405 P403 + P235 P403 + P233	Stateme	ents (Storage): Store locked up. Store in a well-ventilated place. Keep cool. Store in a well-ventilated place. Keep container tightly closed.
Precautionary P501	Stateme	ents (Disposal): Dispose of contents/container to hazardous or special waste collection point.

Revision date: 2014/12/12 Page: 3/11 Version: 3.0 (30090849/CDU_GEN_US/EN)

Hazards not otherwise classified

No applicable information available.

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview
FLAMMABLE LIQUID
HARMFUL IF INHALED
CAN CAUSE CENTRAL NERVOUS SYSTEM DAMAGE
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION
INGESTION MAY CAUSE GASTRIC DISTURBANCES

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number Weight % Chemical name 108-88-3 75.0 - 100.0 % toluene

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number Weight % Chemical name 108-88-3 75.0 - 100.0 % toluene

763-69-9 10.0 - 15.0 % ethyl 3-ethoxypropionate

765 65 5 16.0 16.0 Compt 5 conomptopromate

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air.

If breathing difficulties develop, aid in brea

If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

Immediately wash thoroughly with soap and water. Seek medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

If swallowed:

Revision date : 2014/12/12 Page: 4/11 Version: 3.0 (30090849/CDU_GEN_US/EN)

Rinse mouth and then drink plenty of water.

Do not induce vomiting due to aspiration hazard.

Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

Immediate medical attention is required.

Most important symptoms and effects, both acute and delayed

Symptoms:

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: Dry extinguishing media Carbon dioxide Foam Water spray

Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritants and/or toxic. If product is heated above decomposition temperatures, acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Vapors are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Flash fire may occur.

Remove product from areas of fire or otherwise cool sealed containers with water in order to avoid pressure build-up due to heat

Do not flood burning material with water due to potential spreading of fire.

 ${\tt Contain \ contaminated \ water/firefighting \ water.}$

Revision date : 2014/12/12 Page: 5/11 Version: 3.0 (30090849/CDU_GEN_US/EN)

Run-off water from fire may cause pollution. Notify proper authorities.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Extinguish sources of ignition nearby and downwind.

Wear suitable personal protective clothing and equipment.

Ensure adequate ventilation.

Avoid prolonged inhalation.

Avoid contact with skin and eyes.

Use antistatic tools.

Environmental precautions

Do not discharge into drains/surface waters/groundwater. A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

Methods and material for containment and cleaning up Dike spillage.

Place into appropriately labeled waste containers. Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure adequate ventilation.

Do not puncture, drop or slide containers.

Use static lines when mixing and transferring material.

Handle and open container with care.

Avoid contact with the skin, eyes and clothing.

WARNING: Empty containers may still contain hazardous residue.

Do not apply to hot surfaces.

Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces.

Protection against fire and explosion:

Use antistatic tools.

Exhaust fans should be explosion proof.

Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources

Sealed containers should be protected against heat as this results in pressure build-up.

Risk of explosion if heated under confinement.

Avoid all sources of ignition: heat, sparks, or open flame.

Conditions for safe storage, including any incompatibilities

Segregate from incompatible substances.

Segregate from oxidizing agents.

Segregate from strong bases.

Segregate from strong acids.

Further information on storage conditions:

Revision date : 2014/12/12 Page: 6/11 Version: 3.0 (30090849/CDU_GEN_US/EN)

Keep container tightly closed. Protect from direct sunlight.

Protect from temperatures above 49C/ 120F.

Consult local fire marshal for storage requirements.

Storage stability:

8. Exposure Controls and Personal Protection

Components with occupational exposure limits

toluene

ACGIH TWA 20 ppm

OSHA CLV 300 ppm; TWA 200 ppm; max. conc. 500 ppm

Advice on system design:

General mechanical ventilation should comply with OSHA 1910.94.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear NIOSH-certified (or equivalent) organic vapor respirator. Particulate filters should be added during spray operations. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:

Use appropriate chemically resistant gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen based on activity level and exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and eye wash.

Contact lenses should not be worn.

Remove contaminated clothing.

Contaminated equipment or clothing should be cleaned after each use or disposed of.

Hands and/or face should be washed before breaks and at the end of the $\sinh it$.

9. Physical and Chemical Properties

Form: liquid

Odour: No applicable information available.

Odour threshold: No applicable information available.

Colour: clear

Revision date : 2014/12/12 Page: 7/11 Version: 3.0 (30090849/CDU_GEN_US/EN)

pH value: No applicable information available. Melting temperature: No applicable information available. Boiling range: 230 - 338 °F / 110.0 - 170.0 °C No applicable information available. Sublimation temperature: Flash point: 43 °F (6.1 °C) +/- 3 °F Setaflash Closed Cup (measured) Flammability: No applicable information available. Lower explosion limit: 1.0 %(V) Upper explosion limit: 7.0 %(V) No applicable information available. Autoignition: 20.53 mmHg (20 °C) Vapour pressure: 7.31 Lb/USg CALC Density: Relative density: 0.88 Vapour density: heavier than air Partitioning coefficient n-octanol/water (log Pow): No applicable information available. n-octanol/wass_ Thermal decomposition: No applicable information available. Viscosity, dynamic: No applicable information available. Solids content: approx. 0 % Viscosity, kinematic: > 20.60 mm2/sSolubility in water: No applicable information available. % volatiles: approx. 100.0 %(V) Solubility (quantitative): No applicable information available. Solubility (qualitative): No applicable information available. Evaporation rate: No applicable information available. Total VOC: 876 g/l / 7.3 Lb/USg VOC (minus water and exempt solvent): 876 g/l / 7.3 Lb/USg Weight of VOC (per volume of material): 876 g/l / 7.3 Lb/USg

10. Stability and Reactivity

Reactivity

Reactivity:

No applicable information available.

Chemical stability

Chemical stability:

The product is chemically stable.

Possibility of hazardous reactions

Hazardous reactions:

No applicable information available.

Conditions to avoid

Conditions to avoid:

Avoid all sources of ignition: heat, sparks or open flames.

Avoid electrostatic discharge.

Incompatible materials

Substances to avoid: strong bases strong oxidizing agents

Revision date : 2014/12/12 Page: 8/11
Version: 3.0 (30090849/CDU_GEN_US/EN)

strong acids

Hazardous decomposition products

Decomposition products: carbon monoxide carbon dioxide

Thermal decomposition:
No applicable information available.

11. Toxicological Information

Primary routes of exposure Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: No applicable information available. Oral

Acute oral toxicity:

Inhalation

Acute inhalation toxicity:

Dermal

Acute dermal toxicity:

Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation.

Sensitization

Assessment of sensitization: No applicable information available.

Aspiration hazard No applicable information available.

Chronic Toxicity/Effects

Revision date : 2014/12/12 Page: 9/11 Version: 3.0 (30090849/CDU_GEN_US/EN)

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Genetic toxicity

Assessment of mutagenicity: No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: No applicable information available.

Reproductive toxicity

Assessment of reproduction toxicity: No applicable information available.

Development

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

No applicable information available.

13. Disposal Considerations

Waste disposal of substance Dispose of in accordance with national, state and local regulations.

The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA. Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA licensed facility. Do not incinerate closed containers.

Container disposal

WARNING: Empty containers may still contain hazardous residue. Dispose of in accordance with national, state and local regulations.

14. Transport Information

Revision date: 2014/12/12 Page: 10/11
Version: 3.0 (30090849/CDU_GEN_US/EN)

Reference Bill of Lading

Land transport USDOT

Sea transport IMDG

Air transport IATA/ICAO

15. Regulatory Information

Federal Regulations

Registration status

TSCA, US released / listed

EPCRA 313

CAS number Weight % Chemical name

108-88-3 89.5 toluene

State regulations

State RTK

CAS Number Chemical name

108-88-3 toluene

763-69-9 ethyl 3-ethoxypropionate 64365-23-7 Siloxanes and Silicones, di-Me, hydroxy-terminated,

ethoxyla

71-43-2 benzene

CA Prop. 65

WARNING: This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

HMIS III rating

Health: 2^{p} Flammability: 3 Physical hazard: 0

16. Other information

SDS prepared by: BASF NA Product Regulations SDS prepared on 2014/12/12

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and

Revision date : 2014/12/12 Page: 11/11 Version: 3.0 (30090849/CDU_GEN_US/EN)

minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.