

Safety Data Sheet acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

1 Identification

- Product identifier
- Trade name: SMT3932 SMART DTM Primer Olive Green
- Article number: *SMT3932*
- Application of the substance / the mixture *Coating*
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
Distributed By:
FinishMaster, Inc.
115 W. Washington St., Suite 700S
Indianapolis, IN 46204
317-237-3678.
- Information department: *317 237 3678*
- Emergency telephone number: *INFOTRAC 1-800-535-5053*

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS04 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

*acetone**toluene**Naphtha (petroleum), hydrodesulfurized heavy
butanone*

· Hazard statements

*H222 Extremely flammable aerosol.**H280 Contains gas under pressure; may explode if heated.**H315 Causes skin irritation.**H319 Causes serious eye irritation.**H361 Suspected of damaging fertility or the unborn child.**H336 May cause drowsiness or dizziness.**H373 May cause damage to organs through prolonged or repeated exposure.**H304 May be fatal if swallowed and enters airways.*

· Precautionary statements

*P201 Obtain special instructions before use.**P202 Do not handle until all safety precautions have been read and understood.**P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**P211 Do not spray on an open flame or other ignition source.**P251 Pressurized container: Do not pierce or burn, even after use.**P260 Do not breathe dust/fume/gas/mist/vapors/spray.**P264 Wash thoroughly after handling.**P271 Use only outdoors or in a well-ventilated area.**P280 Wear protective gloves/protective clothing/eye protection/face protection.**P301+P310 If swallowed: Immediately call a poison center/doctor.**P321 Specific treatment (see on this label).**P331 Do NOT induce vomiting.**P302+P352 If on skin: Wash with plenty of water.**P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.**P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P308+P313 IF exposed or concerned: Get medical advice/attention.**P312 Call a poison center/doctor if you feel unwell.**P314 Get medical advice/attention if you feel unwell.**P362+P364 Take off contaminated clothing and wash it before reuse.**P332+P313 If skin irritation occurs: Get medical advice/attention.**P337+P313 If eye irritation persists: Get medical advice/attention.**P403+P233 Store in a well-ventilated place. Keep container tightly closed.**P405 Store locked up.**P410+P403 Protect from sunlight. Store in a well-ventilated place.*

(Contd. on page 3)

USA

Safety Data Sheet acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 2)

P410+P412
P501

*Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/
international regulations.*

- Classification system:
- NFPA ratings (scale 0 - 4)



Health = 2
Fire = 4
Reactivity = 3

- HMIS-ratings (scale 0 - 4)



Health = 2
Fire = 4
Reactivity = 3

- Other hazards
- Results of PBT and vPvB assessment
- PBT: *Not applicable.*
- vPvB: *Not applicable.*

* 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description:
*Mixture: consisting of the following components.
Weight percentages*

- Dangerous components:

67-64-1 acetone	40-60%
68476-86-8 Petroleum gases, liquefied, sweetened	13-30%
108-88-3 toluene	10-13%
78-93-3 butanone	1.5-5%
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene	1.5-5%
110-19-0 isobutyl acetate	1.5-5%
763-69-9 ethyl 3-ethoxypropionate	1-1.5%
108-65-6 2-methoxy-1-methylethyl acetate	1-1.5%

* 4 First-aid measures

- Description of first aid measures
- After inhalation:
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: *Immediately wash with water and soap and rinse thoroughly.*
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: *If symptoms persist consult doctor.*

(Contd. on page 4)

USA



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 3)

- Information for doctor:
- Most important symptoms and effects, both acute and delayed
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

* 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture *No further relevant information available.*
- Advice for firefighters
- Protective equipment: *Wear self-contained respiratory protective device.*

* 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: *Do not allow to enter sewers/ surface or ground water.*
- Methods and material for containment and cleaning up:
*Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.*
- Reference to other sections
*See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.*
- Protective Action Criteria for Chemicals
- PAC-1:

67-64-1 acetone: 200 ppm

108-88-3 toluene: 67 ppm

78-93-3 butanone: 200 ppm

110-19-0 isobutyl acetate: 450 ppm

763-69-9 ethyl 3-ethoxypropionate: 1.6 ppm

108-65-6 2-methoxy-1-methylethyl acetate: 50 ppm

13463-67-7 titanium dioxide: 30 mg/m³

2807-30-9 2-(propyloxy)ethanol: 2.2 ppm

1330-20-7 xylene: 130 ppm

112926-00-8 precipitated Silica (Silica-Amorphous): 18 mg/m³

1333-86-4 Carbon black: 9 mg/m³

100-41-4 ethylbenzene: 33 ppm

67-56-1 methanol: 530 ppm

14302-13-7 PHTHALO GREEN PIGMENT: 12 mg/m³

95-63-6 1,2,4-trimethylbenzene: 140 ppm

(Contd. on page 5)

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 4)

70657-70-4 2-methoxypropyl acetate: 50 ppm
7631-86-9 silicon dioxide, chemically prepared: 18 mg/m³
78-83-1 butanol: 150 ppm
57-55-6 Methyl glycol: 30 mg/m³

· PAC-2:

67-64-1 acetone: 3200* ppm
108-88-3 toluene: 560 ppm
78-93-3 butanone: 2700* ppm
110-19-0 isobutyl acetate: 1300* ppm
763-69-9 ethyl 3-ethoxypropionate: 18 ppm
108-65-6 2-methoxy-1-methylethyl acetate: 1,000 ppm
13463-67-7 titanium dioxide: 330 mg/m³
2807-30-9 2-(propyloxy)ethanol: 24 ppm
1330-20-7 xylene: 920* ppm
112926-00-8 precipitated Silica (Silica-Amorphous): 200 mg/m³
1333-86-4 Carbon black: 99 mg/m³
100-41-4 ethylbenzene: 1100* ppm
67-56-1 methanol: 2,100 ppm
14302-13-7 PHTHALO GREEN PIGMENT: 130 mg/m³
95-63-6 1,2,4-trimethylbenzene: 360 ppm
70657-70-4 2-methoxypropyl acetate: 1,000 ppm
7631-86-9 silicon dioxide, chemically prepared: 740 mg/m³
78-83-1 butanol: 1,300 ppm
57-55-6 Methyl glycol: 1,300 mg/m³

· PAC-3:

67-64-1 acetone: 5700* ppm
108-88-3 toluene: 3700* ppm
78-93-3 butanone: 4000* ppm
110-19-0 isobutyl acetate: 7500** ppm
763-69-9 ethyl 3-ethoxypropionate: 110 ppm
108-65-6 2-methoxy-1-methylethyl acetate: 5000* ppm
13463-67-7 titanium dioxide: 2,000 mg/m³
2807-30-9 2-(propyloxy)ethanol: 140 ppm
1330-20-7 xylene: 2500* ppm
112926-00-8 precipitated Silica (Silica-Amorphous): 1,200 mg/m³
1333-86-4 Carbon black: 590 mg/m³
100-41-4 ethylbenzene: 1800* ppm
67-56-1 methanol: 7200* ppm
14302-13-7 PHTHALO GREEN PIGMENT: 790 mg/m³

(Contd. on page 6)

USA



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 5)

95-63-6 1,2,4-trimethylbenzene: 480 ppm
70657-70-4 2-methoxypropyl acetate: 5,000 ppm
7631-86-9 silicon dioxide, chemically prepared: 4,500 mg/m³
78-83-1 butanol: 8000* ppm
57-55-6 Methyl glycol: 7,900 mg/m³

* 7 Handling and storage

- Handling:
 - Precautions for safe handling *No special measures required.*
 - Information about protection against explosions and fires:
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- Conditions for safe storage, including any incompatibilities
- Storage:
 - Requirements to be met by storerooms and receptacles:
Observe official regulations on storing packagings with pressurized containers.
 - Information about storage in one common storage facility: *Store away from oxidizing agents.*
 - Further information about storage conditions: *Keep receptacle tightly sealed.*
 - Specific end use(s) *No further relevant information available.*

* 8 Exposure controls/personal protection

- Additional information about design of technical systems: *No further data; see item 7.*
- Control parameters
- Components with limit values that require monitoring at the workplace:
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.
 - 67-64-1 acetone
 - PEL Long-term value: 2400 mg/m³, 1000 ppm
 - REL Long-term value: 590 mg/m³, 250 ppm
 - TLV Short-term value: 1187 mg/m³, 500 ppm
 - Long-term value: 594 mg/m³, 250 ppm
 - BEI
 - 108-88-3 toluene
 - PEL Long-term value: 200 ppm
 - Ceiling limit value: 300; 500* ppm
 - *10-min peak per 8-hr shift
 - REL Short-term value: 560 mg/m³, 150 ppm
 - Long-term value: 375 mg/m³, 100 ppm

(Contd. on page 7)

USA

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 6)

TLV Long-term value: 75 mg/m³, 20 ppm
BEI

78-93-3 butanone

PEL Long-term value: 590 mg/m³, 200 ppm

REL Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
BEI

110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m³, 150 ppm

REL Long-term value: 700 mg/m³, 150 ppm

TLV Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L

Medium: urine

Time: end of shift

Parameter: Toluene

0.3 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L

Medium: urine

Time: end of shift

Parameter: MEK

Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 8)

USA

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 7)

- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.*
 - Immediately remove all soiled and contaminated clothing.*
 - Wash hands before breaks and at the end of work.*
 - Store protective clothing separately.*
 - Avoid contact with the eyes and skin.*
- Breathing equipment:
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*
- Protection of hands:
 - Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*
 - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Material of gloves
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*
- Penetration time of glove material
 - The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.*
- Eye protection:
 - Safety glasses*



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- General Information
- Appearance:
 - Form: *Aerosol*
 - Color: *According to product specification*
- Odor: *Characteristic*
- Odor threshold: *Not determined.*

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 8)

- pH-value: *Not determined.*
- Change in condition
 - Melting point/Melting range: *Undetermined.*
 - Boiling point/Boiling range: *55 °C*
- Flash point: *-103 °C*
- Flammability (solid, gaseous): *Not applicable.*
- Ignition temperature: *465 °C*
- Decomposition temperature: *Not determined.*
- Auto igniting: *Product is not selfigniting.*
- Danger of explosion: *In use, may form flammable/explosive vapour-air mixture. Avoid high heat*
- Explosion limits:
 - Lower: *1.2 Vol %*
 - Upper: *13 Vol %*
- Vapor pressure at 20 °C: *233 hPa*
- Density at 20 °C: *0.7528 g/cm³*
- Relative density: *Not determined.*
- Vapor density: *Not determined.*
- Evaporation rate: *Not applicable.*
- Solubility in / Miscibility with Water: *Not miscible or difficult to mix.*
- Partition coefficient (n-octanol/water): *Not determined.*
- Viscosity:
 - Dynamic: *Not determined.*
 - Kinematic: *Not determined.*
- Solvent content:
 - Organic solvents: *89.5 %*
 - Water: *0.0 %*
 - VOC content: *46.04 %*
580.4 g/l / 4.84 lb/gl
- Solids content: *10.4 %*
- Other information: *No further relevant information available.*

10 Stability and reactivity

- Reactivity *No further relevant information available.*
- Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- Possibility of hazardous reactions *No dangerous reactions known.*
- Conditions to avoid *No further relevant information available.*

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 9)

- Incompatible materials: *No further relevant information available.*
- Hazardous decomposition products:
 - Nitrogen oxides*
 - Hydrocarbons*
 - Carbon monoxide and carbon dioxide*

* 11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

 - 108-88-3 toluene*
 - Oral LD50 5,000 mg/kg (rat)*
 - Dermal LD50 12,124 mg/kg (rabbit)*
 - Inhalative LC50/4 h 5,320 mg/l (mouse)*
 - Primary irritant effect:
 - on the skin: *Irritant to skin and mucous membranes.*
 - on the eye: *Irritating effect.*
 - Sensitization: *No sensitizing effects known.*
 - Additional toxicological information:
 - The product shows the following dangers according to internally approved calculation methods for preparations:*
 - Irritant*
- Carcinogenic categories
- IARC (International Agency for Research on Cancer)

 - 108-88-3 toluene: 3*
 - 13463-67-7 titanium dioxide: 2B*
 - 1330-20-7 xylene: 3*
 - BENTONITE: suspected carcinogen <2% 14808-60-7*
 - 1333-86-4 Carbon black: 2B*
 - 100-41-4 ethylbenzene: 2B*
 - 7631-86-9 silicon dioxide, chemically prepared: 3*
- NTP (National Toxicology Program)

 - None of the ingredients is listed.*
- OSHA-Ca (Occupational Safety & Health Administration)

 - 68911-87-5 montmorillonite clay complex*

12 Ecological information

- Toxicity
- Aquatic toxicity: *No further relevant information available.*
- Persistence and degradability *No further relevant information available.*
- Behavior in environmental systems:
- Bioaccumulative potential *No further relevant information available.*
- Mobility in soil *No further relevant information available.*

(Contd. on page 11)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 10)

- Additional ecological information:
- General notes:
 - Water hazard class 3 (Self-assessment): extremely hazardous for water*
 - Do not allow product to reach ground water, water course or sewage system, even in small quantities.*
 - Danger to drinking water if even extremely small quantities leak into the ground.*
- Results of PBT and vPvB assessment
- PBT: *Not applicable.*
- vPvB: *Not applicable.*
- Other adverse effects *No further relevant information available.*

13 Disposal considerations

- Waste treatment methods
- Recommendation:
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- Uncleaned packagings:
- Recommendation: *Disposal must be made according to official regulations.*

* 14 Transport information

- UN-Number
 - DOT, ADR, IMDG, IATA
 - UN proper shipping name
 - DOT
 - ADR
 - IMDG
 - IATA
 - Transport hazard class(es)
- | | |
|--|----------------------------|
| | <i>UN1950</i> |
| | <i>Aerosols, flammable</i> |
| | <i>1950 Aerosols</i> |
| | <i>AEROSOLS</i> |
| | <i>AEROSOLS, flammable</i> |

- DOT



- Class
 - Label
- | | |
|--|------------|
| | <i>2.1</i> |
| | <i>2.1</i> |

- ADR



- Class
- | | |
|--|-------------------|
| | <i>2 5F Gases</i> |
|--|-------------------|

(Contd. on page 12)

USA

Safety Data Sheet
acc. to OSHA HCS


Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 11)

· Label	2.1

· IMDG, IATA	
	
· Class	2.1
· Label	2.1
· Packing group	
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Gases
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

· ADR	
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

USA

(Contd. on page 13)

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 12)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- Sara

- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

- Section 313 (Specific toxic chemical listings):

108-88-3 toluene

Acrylic Resin

78-93-3 butanone

1330-20-7 xylene

100-41-4 ethylbenzene

67-56-1 methanol

95-63-6 1,2,4-trimethylbenzene

- TSCA (Toxic Substances Control Act):

67-64-1 acetone

108-88-3 toluene

78-93-3 butanone

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

110-19-0 isobutyl acetate

763-69-9 ethyl 3-ethoxypropionate

108-65-6 2-methoxy-1-methylethyl acetate

13463-67-7 titanium dioxide

16883-83-3 benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate

2807-30-9 2-(propyloxy)ethanol

51274-00-1 YELLOW IRON OXIDE

1330-20-7 xylene

1333-86-4 Carbon black

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

68911-87-5 montmorilontie clay complex

100-41-4 ethylbenzene

61791-55-7 Amines, N-tallow alkyltrimethylenedi-

67-56-1 methanol

14302-13-7 PHTHALO GREEN PIGMENT

95-63-6 1,2,4-trimethylbenzene

7631-86-9 silicon dioxide, chemically prepared

78-83-1 butanol

57-55-6 Methyl glycol

7732-18-5 water

- TSCA new (21st Century Act) (Substances not listed)

68476-86-8 Petroleum gases, liquefied, sweetened

(Contd. on page 14)

USA

Safety Data Sheet acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 13)

- Proposition 65
- Chemicals known to cause cancer:

 - 13463-67-7 titanium dioxide
 - 1330-20-7 xylene
 - 1333-86-4 Carbon black
 - 100-41-4 ethylbenzene
 - 95-63-6 1,2,4-trimethylbenzene
- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.
- Chemicals known to cause developmental toxicity:

 - 108-88-3 toluene
 - 67-56-1 methanol
- Cancerogenity categories
- EPA (Environmental Protection Agency)

 - 67-64-1 acetone: I
 - 108-88-3 toluene: II
 - 78-93-3 butanone: I
 - 1330-20-7 xylene: I
 - 100-41-4 ethylbenzene: D
 - 95-63-6 1,2,4-trimethylbenzene: II
- TLV (Threshold Limit Value established by ACGIH)

 - 67-64-1 acetone: A4
 - 108-88-3 toluene: A4
 - 13463-67-7 titanium dioxide: A4
 - 1330-20-7 xylene: A4
 - 1333-86-4 Carbon black: A4
 - 100-41-4 ethylbenzene: A3
- NIOSH-Ca (National Institute for Occupational Safety and Health)

 - 13463-67-7 titanium dioxide
 - 1333-86-4 Carbon black
 - 67-56-1 methanol
- GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02 GHS04 GHS07 GHS08

- Signal word *Danger*

(Contd. on page 15)

USA

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 14)

- Hazard-determining components of labeling:
 - acetone
 - toluene
 - Naphtha (petroleum), hydrodesulfurized heavy
 - butanone
- Hazard statements
 - H222 *Extremely flammable aerosol.*
 - H280 *Contains gas under pressure; may explode if heated.*
 - H315 *Causes skin irritation.*
 - H319 *Causes serious eye irritation.*
 - H361 *Suspected of damaging fertility or the unborn child.*
 - H336 *May cause drowsiness or dizziness.*
 - H373 *May cause damage to organs through prolonged or repeated exposure.*
 - H304 *May be fatal if swallowed and enters airways.*
- Precautionary statements
 - P201 *Obtain special instructions before use.*
 - P202 *Do not handle until all safety precautions have been read and understood.*
 - P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
 - P211 *Do not spray on an open flame or other ignition source.*
 - P251 *Pressurized container: Do not pierce or burn, even after use.*
 - P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*
 - P264 *Wash thoroughly after handling.*
 - P271 *Use only outdoors or in a well-ventilated area.*
 - P280 *Wear protective gloves/protective clothing/eye protection/face protection.*
 - P301+P310 *If swallowed: Immediately call a poison center/doctor.*
 - P321 *Specific treatment (see on this label).*
 - P331 *Do NOT induce vomiting.*
 - P302+P352 *If on skin: Wash with plenty of water.*
 - P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
 - P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
 - P308+P313 *IF exposed or concerned: Get medical advice/attention.*
 - P312 *Call a poison center/doctor if you feel unwell.*
 - P314 *Get medical advice/attention if you feel unwell.*
 - P362+P364 *Take off contaminated clothing and wash it before reuse.*
 - P332+P313 *If skin irritation occurs: Get medical advice/attention.*
 - P337+P313 *If eye irritation persists: Get medical advice/attention.*
 - P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
 - P405 *Store locked up.*
 - P410+P403 *Protect from sunlight. Store in a well-ventilated place.*
 - P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*
 - P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*
- Chemical safety assessment: *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 16)

USA

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 03/14/2018

Reviewed on 11/01/2016

Trade name: SMT3932 SMART DTM Primer Olive Green

(Contd. of page 15)

- Department issuing SDS: *Environment protection department.*
- Contact: **317-237-3678.**
- Date of preparation / last revision **03/14/2018 / 13**
- Abbreviations and acronyms:
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
 - ICAO: International Civil Aviation Organisation*
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
 - IMDG: International Maritime Code for Dangerous Goods*
 - DOT: US Department of Transportation*
 - IATA: International Air Transport Association*
 - ACGIH: American Conference of Governmental Industrial Hygienists*
 - EINECS: European Inventory of Existing Commercial Chemical Substances*
 - ELINCS: European List of Notified Chemical Substances*
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)*
 - NFPA: National Fire Protection Association (USA)*
 - HMIS: Hazardous Materials Identification System (USA)*
 - VOC: Volatile Organic Compounds (USA, EU)*
 - LC50: Lethal concentration, 50 percent*
 - LD50: Lethal dose, 50 percent*
 - PBT: Persistent, Bioaccumulative and Toxic*
 - vPvB: very Persistent and very Bioaccumulative*
 - NIOSH: National Institute for Occupational Safety*
 - OSHA: Occupational Safety & Health*
 - TLV: Threshold Limit Value*
 - PEL: Permissible Exposure Limit*
 - REL: Recommended Exposure Limit*
 - BEI: Biological Exposure Limit*
 - Flam. Aerosol 1: Aerosols – Category 1*
 - Press. Gas: Gases under pressure – Compressed gas*
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2*
 - Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*
 - Repr. 2: Reproductive toxicity – Category 2*
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*
 - STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*
 - Asp. Tox. 1: Aspiration hazard – Category 1*
- * Data compared to the previous version altered.

USA