



**TECHNICAL DATA SHEET**  
SMT3942 SMART Aerosol Blender

Distributed by:  
FinishMaster, Inc.  
115 W. Washington  
Street  
Suite 700 S  
Indianapolis, IN 46204  
317-237-3678

**COMPONENTS**

SMT3942 SMART AEROSOL BLENDER

**DESCRIPTION**

SMT3942 is a fade out blender solvent specially formulated to assist in dissolving the dry edges of freshly sprayed clearcoats and topcoats.

- Allows repairs to be confined to a single panel and blended in
- Invisible blend finish
- For use with all coatings
- Suitable for smart repairs

**INSTRUCTIONS FOR USE**

1. Shake the aerosol can for at least 2 minutes before use.
2. Holding the aerosol approximately 10 inches from the panel, apply a light mist coat over the blend area of the freshly applied clearcoat or topcoat.
3. Two rapid passes of the aerosol will give an ideal blending process. The dry edge of the repair area will melt into the surrounding original paintwork, this will minimize the need for further processing once the clearcoat or topcoat has cured.
4. Once SMT3942 is applied, follow the clearcoat or topcoat manufacturer's instructions for flash off and drying.

**STORAGE & VOC INFORMATION**

**Shelf Life**

- 2 years subject to good storage conditions
- Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximize the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.
- *Recommended Storage Temperature: 40°F - 80°F*
- *Recommended Application Temperature: 40°F - 95°F*

**VOC Information**

Order Code	Format	Color	MIR
SMT3942	12oz Aerosol	Clear	N/A

**IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.**