



TECHNICAL DATA SHEET
SMT3990 SMART Powder Guide Coat

Distributed by:
FinishMaster, Inc.
115 W. Washington
Street
Suite 700 S
Indianapolis, IN 46204
317-237-3678

COMPONENTS

SMT3990 SMART POWDER GUIDE COAT

DESCRIPTION

SMT3990 is used to expose low spots and imperfections during surface preparation

- Does not clog or block abrasives
- Suitable for wet or dry sanding
- Dries instantly

TECHNICAL DATA

Mixing

1. Shake the aerosol can for at least 2 minutes before use.
2. Spray directly onto the cured bodyfiller or primer, SMT3990 dries in seconds, sand to required finish any low spots will show as black.

STORAGE & VOC INFORMATION

Shelf Life

- 2 years subject to good storage conditions
Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximize the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.
- *Recommended Storage Temperature: 40°F - 80°F*
- *Recommended Application Temperature: 40°F - 95°F*

VOC Information

Order Code	Format	Color	MIR
SMT3990	12oz Aerosol	Black	PAP 2.5

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.