



ADHESION PROMOTER

Technical Data

| BULLDOG® ADHESION PROMOTER | |
|-----------------------------------|---|
| Appearance | Liquid, Hazy, Light Pink to Light Yellow, Mobile, Dries to a Class A Water-white Finish |
| Vapor Density | Heavier than Air |
| Percent Volatile | 82.75% by weight |
| Flash Point | 32°F |
| CPSC Flammability Classification | Flammable |
| MAX V.O.C. | 748 grams/liter (6.23 lb/gal) |
| MAX Vapor Pressure of the V.O.C. | 30.6mm Hg at 20°C |
| Storage | Store between 32°F and 95°F, in the original container. |
| Coverage | up to 750 sq. ft. per gallon |
| Shelf Life | 2 years from date of manufacture, in an unopened container |
| DOT | UN1866, Resin Solution, Flammable, 3, PGII |
| HAPS | Toluene, Xylene, Ethyl Benzene, Styrene |
| VOC Category | Specialty Coatings |
| Density | 7.5 lbs/gal |
| Boiling Range | 132°F to 380°F |

PREPARING PLASTIC PARTS FOR PAINTING



Ordering Information

| PRODUCT | SIZE | PACK | LBS | CUBE FT. | WIDTH | DEPTH | HEIGHT | UPC CODE | PALLET QTY. |
|---------|------|------|-----|----------|----------------------------------|---------------------------------|----------------------------------|---------------|-------------|
| PTPO123 | PT | 12 | 15 | .438 | 11 ¹ / ₁₆ | 8 ⁹ / ₁₆ | 8 | 03019212310-2 | 90 CASES |
| QTPO123 | QT | 6 | 14 | .406 | 10 ⁹ / ₁₆ | 7 ¹ / ₈ | 9 ⁵ / ₁₆ | 03019212315-7 | 88 CASES |
| GTPO123 | GL | 4 | 36 | .762 | 13 ¹³ / ₁₆ | 8 ¹³ / ₁₆ | 10 ¹³ / ₁₆ | 03019212325-6 | 52 CASES |



Carefully read all cautions and instructions on product label before use.
For more information about other Klean-Strip products, call or write Klean-Strip Marketing department.

www.kleanstripauto.com

©2007 W.M. Barr & Co., Inc. PO Box 1879, Memphis, TN 38101 Phone: (800) 238-2672 Fax: (800) 621-9508