



GRAVIGARD

Chip Guard Aerosol

Description

GRAVIGARD is a tough, hard, durable coating designed to reproduce the manufacturer's original stone chip finish. **GRAVIGARD** will protect against stone chips, salt, damp and rust.

GRAVIGARD will also help to deaden sound and vibrations and is, therefore, ideal for application to body panels and inside engine compartments. The high build formula will cover weld marks and seams, often in one application.

Health and Safety Statement

FOR PROFESSIONAL USE ONLY. Read full instructions before use.

IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM.

U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

Surface preparation and instructions for use

GRAVIGARD chip guard aerosol can be used on the following surfaces:-

- Suitably prepared, primed or bare metal. For overcoating aluminum, an etch primer is recommended.
- Fully cured paint surfaces.

Thoroughly clean and degrease old paint surfaces with a suitable spirit wipe or thinner. Wet flat with 400 grade paper. For bare metal use 180 grade paper. Re-clean and dry.

Application

Shake the can before use. Allow approximately 10-15 mins. for the solvent to flash off when building a thick coat.

Build

One coat of **GRAVIGARD** will give a build of approximately 2 thou. Spray the **GRAVIGARD** at a distance of 8 -12 in. from the panel being coated. Varying the distance of the can from the panel during spraying will give a flatter or bumpier effect.

Drying time

Approximately 2 hours at normal shop temperature or 30 mins. at low bake (180°F). Drying time is dependent on film thickness, humidity and temperature.

Over-painting

GRAVIGARD may be over painted with most paint systems. With 2 pack acrylic paints its can be over-painted wet on wet. For optimum gloss the use of a primer is recommended.

Product codes

- UP 731 - Black color / 500ml Aerosol.
UP 732 - Gray color / 500ml Aerosol.

U-POL US, Inc., 630 Selvaggio Dr, Suite 300, Nazareth, PA 18064
Tel: (800) 340 7824; Fax: (800) 787 5150
Email: sales-us@u-pol.com Website: www.u-pol.com