



TECHNICAL BULLETIN

GOLD TEAK OIL

Protects teak, rejuvenating the rich, natural golden wood colors. Prevents drying out of wood from exposure to the elements. Great for bulkheads, hatch covers, swim steps, guard rails and decking.

Part #: M-4616– 16 fl oz

Packaging: 16 fl. oz - 6 per case

Features:

- Cleans and conditions teak
- Restores rich, golden color and fights weathering
- Will not break down the polysulfide caulking on teak decks

pH: N/A

Paintable: Yes

Dilution: RTU (Ready to use)

Application Method: Wipe on, wipe dry

Directions: Before applying, surface should be clean and dry. Badly stained teak may need to be treated with a bleach cleaner before applying Gold Teak Oil. Do not apply in extreme heat or cold. SHAKE WELL. Dispense liberal amount on 100% cotton, terry towel or applicator pad and rub thoroughly into wood. Wipe dry with separate towel. For maximum protection, apply three coats, allowing a day of sun on each coat.

Health rating:

Health:	1
Fire:	0
Reactivity:	0
Specific Hazard:	N/A

Scale: 4 = Extreme, 3 = High,
2 = Moderate, 1 = Slight, 0 = Insignificant

**FOR ADDITIONAL SAFETY INFORMATION, CONSULT MSDS
KEEP OUT OF REACH OF CHILDREN**