

(i) Check local VOC regulations to ensure compliance of all products in your area.

# DESCRIPTION

**Quick Set 50** is a very fast, two-component black urethane adhesive designed for automotive plastic repair and bonding most small plastic, steel and aluminum parts.

# **FEATURES**

- **DUAL-MIX™** Forever Warranty
- High strength and sandable
- · Bonds almost anything
- Non-sag formula fills gaps
- 15 minute cure

# **SUITABLE SUBSTRATES**

- Plastic
- Steel
- Aluminum

# **TYPICAL PROPERTIES**

| Part:         | Product Name: | Color: Container:        |
|---------------|---------------|--------------------------|
| 40502         | Quick Set 50  | Black 1.7 oz. Cartridge  |
| 40507         | Quick Set 50  | Black 7 oz. Cartridge    |
| Working time: |               | 45 seconds @ 70°F (21°C) |
| Set time:     |               | 50 seconds @ 70°F (21°C) |
| Cure time:    |               | 15 minutes @ 70°F (21°C) |
| Lap shear:    |               | 2300+psi @ 70°F (21°C)   |

Check local VOC regulations to ensure compliance of all products in your area.

# HANDLING AND APPLICATION

### **PREPARATION:**

### FOR PLASTIC:

- 1. Clean with Scuff & Clean and rinse with water.
- 2. Clean with Plastic & Leather Prep or XXX Universal Surface Cleaner.
- 3. Sand area to be repaired with 24-36 grit paper and blow off dust.
- **4.** For application on TPO, EPDM, PP and other similar thermoplastics, use **Plastic Adhesion Promoter** or **XXX Adhesion Promoter** per instructions.

### FOR METAL:

- 1. Clean with SEM Solve or XXX Universal Surface Cleaner.
- **2.** Sand with 80 grit paper and blow off dust.
- 3. Re-clean with SEM Solve or XXX Universal Surface Cleaner.

### **MIXING:**

Place cartridge into the **Universal Manual Applicator** or the **1.7 oz. Manual Applicator**. To remove cap, insert flat head screwdriver into slot and pry upward.

### Note:

For cap replacement, match circles and square, and snap back into place. When using 1.7 oz. cartridges, twist the blue retaining nut and remove. Prior to installing static mixer, equalize cartridge by dispensing product until both parts flow equally. Install static mixer. Cut tip to desired application size.

### **STATIC MIXERS:**

| Part: | Product Name:                     | For: Container:   |         |
|-------|-----------------------------------|-------------------|---------|
| 70011 | Integral Nut Square Static Mixers | 7 oz. Cartridge   | 6 Pack  |
| 70012 | Integral Nut Square Static Mixers | 7 oz. Cartridge   | 50 Pack |
| 70020 | 1.7 oz Turbo Static Mixers        | 1.7 oz. Cartridge | 6 Pack  |
| 70021 | 1.7 oz Turbo Static Mixers        | 1.7 oz. Cartridge | 50 Pack |

### **APPLICATION:**

### **GENERAL PURPOSE BONDING:**

- **1.** Prepare surface as outlined in Preparation section.
- 2. Dry fit parts to ensure proper alignment.
- 3. For impact strips and side moldings, mask both sides of the surface where adhesive is to be applied.

### Note:

Do not allow Quick Set 50 to flow over masked area or onto painted surface.

- **4.** Apply **Quick Set 50** to either surface.
- 5. Quickly bond the two surfaces. Hold or clamp together until set.

### FOR TAB REPAIR USING PLASTIC REPAIR CONTOURING TAPE:

- **1.** Prepare surface as outlined in Preparation section.
- 2. For badly torn damage, drill 1/8" holes approximately 1/2" apart into the repair area. This will help lock the repair material in place.
- **3.** Cut a piece of **Plastic Repair Contouring Tape** twice the length of the repair.
- **4.** Dispense **Quick Set 50** onto **Plastic Repair Contouring Tape**. Quickly apply both to the repair area and mold into shape using your hands or a spreader.

5. Allow the repair material to cure for 5 minutes before removing the plastic film.

**6.** Sand with a 80-180 grit disc to desired shape and drill as needed.

#### Note:

WORK QUICKLY! The repair material will set in 50 seconds.

### **CAUTION:**

Quick Set 50 can get very hot while curing.

### **STORAGE:**

**Quick Set 50** should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Quick Set 50** is 1 year when stored under optimal conditions.

## **RELATED PRODUCTS**

| Part: | Product Name:                     | Size:          |
|-------|-----------------------------------|----------------|
| 38351 | Plastic & Leather Prep            | Gallon         |
| 38353 | Plastic & Leather Prep            | Aerosol        |
| 38354 | Plastic & Leather Prep            | Quart          |
| 38371 | SEM Solve                         | Gallon         |
| 38373 | SEM Solve                         | 20 oz. Aerosol |
| 38374 | SEM Solve                         | Quart          |
| 38375 | SEM Solve                         | 5 Gallon       |
| 38391 | Scuff & Clean                     | Gallon         |
| 38398 | Scuff & Clean                     | 16 oz. Tube    |
| 39861 | Plastic Adhesion Promoter         | Gallon         |
| 39863 | Plastic Adhesion Promoter         | Aerosol        |
| 39864 | Plastic Adhesion Promoter         | Quart          |
| 77771 | XXX Universal Surface Cleaner     | Gallon         |
| 77774 | XXX Universal Surface Cleaner     | Quart          |
| 70007 | Plastic Repair Contouring Tape    | 15' Roll       |
| 70011 | Integral Nut Square Static Mixers | 6 Pack         |
| 70012 | Integral Nut Square Static Mixers | 50 Pack        |
| 70019 | 1.7 oz Manual Applicator Gun      | 1 Each         |
| 70020 | 1.7 oz Turbo Static Mixers        | 6 Pack         |
| 70021 | 1.7 oz Turbo Static Mixers        | 50 Pack        |
| 71119 | Universal Manual Applicator Gun   | 1 Each         |
| 77721 | XXX Adhesion Promoter             | Gallon         |
|       |                                   |                |

| 77723 | XXX Adhesion Promoter | Aerosol |
|-------|-----------------------|---------|
| 77724 | XXX Adhesion Promoter | Quart   |

#### **Technical Consultation Service**

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

#### **Disclaimer:**

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.