



PRODUCT DATA

4303, 4313

Tex Coat Chip Guard

DESCRIPTION:

Tex Coat is a rapid drying, flexible protective coating. Texture can be varied to match OEM textures as found on rocker panels, valances, etc. 4303 MIR = 1.17, 4313 MIR = 1.16

USE:

Designed for under paint use as an original or replacement texturized coating. Tex Coat may be used under enamels or lacquers.

APPLICATION:

Wash and solvent clean area to remove all dirt, grease, oil and silicone. Use SCAT #6311, Speedi SCAT #6321 or Aqua SCAT #6351/6354. Remove all existing finish. Clean again with SCAT. Prepare bare metal with appropriate Transtar metal primer. Sand with 220 grit. Remove sanding dust with SCAT. Shake Tex Coat can vigorously. Apply in 1-3 light even coats. Film build should be about 3.0 mils percoat. Total film build should not exceed 8-10 mils. Flash 10-15 minutes between coats. IMPORTANT: KEEP CAN IN MOTION WHEN APPLYING TO AVOID EXCESSIVE FILM BUILD. Allow final Tex Coat application to flash 30-60 minutes at 75°F (25°C) before topcoating. Follow manufacturer's instructions before topcoating. Optional: Apply sealer over Tex Coat for optimum performance. A flex additive such as Universal Urethane FlexAdditive #9194 is recommended for topcoats (specifically lacquers).

Helpful Tips: Use a piece of scrap sheet metal to practice spray techniques to match the pattern on the vehicle being refinished. Pattern and amount of texture can be changed by varying the distance of spray can from the substrate being sprayed. Texture pattern/size can be increased by depressing valve only partially. This will permit more texture using less pressure.

SALES POINTS:

- Fast drying.
- Paintable in 30-45 minutes.
- Matches any OEM finish.
- Highly chip resistant.
- Convenient aerosol requires no equipment clean-up.

COMPETITION:

3M Rocker Panel Spray, Rocker Schutz
Morton Mor-Guard
RubberSeal Gravel Guard
SEM Chip Guard



(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin).

PACKAGE SIZE:

4303 Tex Coat (White), 16 oz. aerosol (473 ml), 6/case
4313 Tex Coat (Black), 16 oz. aerosol (473 ml) 6/case

DISCLAIMER: The Technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Transtar Autobody Technologies experience and research and is believed to be reliable. As Transtar has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.