

UP0724, UP0730, UP0762 HARDENER BPO

Page: 1

Compilation date: 13/01/2012

Revision date: 19/07/2012

Revision No: 8

## Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: UP0724, UP0730, UP0762 HARDENER BPO

Product code: HRED/L

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: HARDENER CONTAINING BENZOYL PEROXIDE

### 1.3. Details of the supplier of the safety data sheet

Company name: U-POL US Inc.

630 Selvaggio Drive Suite 300 Nazareth PA 18064 USA Tel: 1-800-340-7824

Tel: 1-000-540-7024

Fax: 1-800-787-5150

Email: technical:u-pol.com

## **1.4. Emergency telephone number**

Emergency tel: 1-800-424-9300 (CHEMTREC)

## Section 2: Hazards identification

2.1. Classification of the substance or mixture				
Classification under CHIP:	O: R7; Xi: R36; Sens.: R43; -: R52/53			
Most important adverse effects:	May cause fire. Irritating to eyes. May cause sensitisation by skin contact. Harmful to			
	aquatic organisms, may cause long-term adverse effects in the aquatic environment.			
Classification under CLP:	This product has no classification under CLP.			

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Irritant.

Oxidising.



Risk phrases: R7: May cause fire.

R36: Irritating to eyes.

## UP0724, UP0730, UP0762 HARDENER BPO

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.Safety phrases: S3/7: Keep container tightly closed in a cool place.

S24: Avoid contact with skin.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

## 2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

### Hazardous ingredients:

DIBENZOYL PEROXIDE

	EINECS	CAS	CHIP Classification	CLP Classification	Percent
2	202-327-6	94-36-0	E: R3; O: R7; Xi: R36; Sens.: R43	Eye Irrit. 2: H319; Skin Sens. 1: H317; Org. Perox. B: H241	30-50%

## DIBUTYL MALEATE

- 105-76-0 Sens.: R43; N: R51/53 -	10-30%
------------------------------------	--------

## Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## UP0724, UP0730, UP0762 HARDENER BPO

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Oxidising.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

# UP0724, UP0730, UP0762 HARDENER BPO

Page: 4

					Fag	
Workplace expo	sure limits:			Respirable dust		
State	8 hour TWA	\	15 min. STEL	8 hour TWA	15 min. STEL	
UK	5 n	ng/m3		1 mg/m3	-	
Hazardous ingr	edients:					
DIBENZOYL PE	ROXIDE					
Workplace expo	osure limits:			Respirable dust		
State	State 8 hour TWA		15 min. STEL	8 hour TWA	15 min. STEL	
UK 5 mg/m3		ng/m3		- <b>-</b>		
.2. Exposure cor	ntrols					
Engineering	measures: En	sure there	e is sufficient ventilation	n of the area.		
Respiratory	protection: Re	Respiratory protection not required.				
Hand	protection: Nit	trile gloves	S.			
Eye protection: Safety goggles. Ensure eye bath is to hand.						
Skin protection: Protective clothing. Rubber apron.						
tion 9: Physica	I and chemic	al prope	rties			
.1. Information o	n basic physic	al and ch	emical properties			
	State: Pa	iste				
	Colour: Re	Red				
	Odour: Ba	Barely perceptible odour				
Evapor	ration rate: Ne	Negligible				
	Oxidising: Ox	Oxidising (by EC criteria)				
Solubilit	y in water: Ins	Insoluble				
	Viscosity: Vis	Viscous				
Kinematic	viscosity: 10	00cps				
Autoflam	mability°C: >3	80		Relative dens	sity: 1.2	
	VOC g/l: 27	4 (2.30 lbs	s/gal)			
.2. Other informa	ition					
Other in	formation: No	ot applicab	le.			
tion 10: Stabili	ty and reactiv	vity				
0.1. Reactivity						
	Reactivity: Sta	able under	recommended transpo	ort or storage conditions.		
0.2. Chemical sta	ability					
Chemic	al stability: Sta	able under	normal conditions. SA	DT (Self-Accelerating Decom	position Temperature)	
Chemic	al stability: Sta	able under	normal conditions. SA	DT (Self-Accelerating Decom	position Temperatu	

## UP0724, UP0730, UP0762 HARDENER BPO

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition.

## 10.5. Incompatible materials

Materials to avoid: Reducing agents. Acids. Bases. Metals.

### **10.6.** Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

#### Section 11: Toxicological information

## 11.1. Information on toxicological effects

#### **Relevant effects for mixture:**

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.Eye contact: There may be irritation and pain.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

## 12.2. Persistence and degradability

## Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

#### 12.4. Mobility in soil

Mobility: Insoluble in water.

### UP0724, UP0730, UP0762 HARDENER BPO

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This substance is not identified as a PBT substance.

#### 12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

## Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Incineration on land.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### Section 14: Transport information

14.1. UN number

UN number: UN3108

14.2. UN proper shipping name

Shipping name: ORGANIC PEROXIDE, TYPE E, SOLID

14.3. Transport hazard class(es)

Transport class: 5.2

14.4. Packing group

## 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

### Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

## UP0724, UP0730, UP0762 HARDENER BPO

453/2010. FOR PROFESSIONAL USE ONLY. Read full instructions before use. IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment. Phrases used in s.2 and 3: H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. R3: Extreme risk of explosion by shock, friction, fire or other sources of ignition. R7: May cause fire. R36: Irritating to eyes. R43: May cause sensitisation by skin contact. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.